




RoHS
Compliant



Color: ■



Data

Electrical data

Ratings per IEC/EN 60664-1

Rated voltage (II / 2)	400 V
Rated impulse voltage (II / 2)	4 kV
Rated current	24 A

Connection data

Connection technology	CAGE CLAMP®
Actuation type	Push-in
Connectable conductor materials	Copper Aluminum
Solid conductor	0.5 ... 2.5 mm² / 20 ... 16 AWG



Fine-stranded conductor	0.5 ... 2.5 mm ² / 20 ... 16 AWG
Strip length	9 ... 11 mm / 0.35 ... 0.43 inch
Total number of connection points	2
Total number of potentials	1
Type of wiring	Side-entry wiring
Leiterquerschnitte eindrhtig	0.5 mm ²

Geometrical Data

Width	8 mm / 0.315 inch
Height	15.5 mm / 0.61 inch
Depth	42 mm / 1.654 inch
Plug width	8 mm / 0.315 inch

Material Data

Color	gray
Fire load	0.099 MJ
Weight	5 g

Commercial data

Country of origin	CH
GTIN	4044918818407
Customs Tariff No.	85369010000

Approvals / Certificates

Country specific Approvals

Logo	Approval	Certificate name
	CSA DEKRA Certification B.V.	1053495
	VDE VDE Prf- und Zertifizierungsinstitut	40022792

Ship Approvals

Logo	Approval	Certificate name
	ABS American Bureau of Shipping	18-HG1755093-PDA
	BV Bureau Veritas S.A.	11914/C0 BV



UL-Approvals

Logo	Approval	Certificate name
	UL UL International Germany GmbH	CCA-DK No. 2527

Compatible products

General accessories

Item no.: 249-130 Syringe; Contents: 20 ml Alu-Plus contact paste	www.wago.com/249-130
--	--

Downloads

CAD/CAE - Smart Data

CAD data

3D Download 224-201	URL	Download
---------------------	-----	----------

Subject to changes.

WAGO Kontakttechnik GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.