

## TKE/P 50



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.

<b>Material cable gland</b>	Polyamide
<b>Material sealing gasket</b>	EPDM
<b>Temp. range min</b>	-40 °C
<b>Temp. range max</b>	100 °C
<b>Protection class</b>	IP66, IP68 (5 bar 30 min)
<b>Product Color</b>	RAL 7035
<b>Thread type</b>	M
<b>Ø Connection thread D</b>	50
<b>Lead</b>	1,5
<b>Length screw-in thread L</b>	14 mm
<b>Key width SW</b>	55 mm
<b>Total length TL</b>	59 mm - 72 mm
<b>Glow wire test</b>	750 °C
<b>Type of cable anchorage</b>	A
<b>Install. torques fitting</b>	30 N/m
<b>Install. torques cap nut</b>	30 N/m
<b>Impact category</b>	5
<b>Order no. RAL 7035</b>	10106246
<b>Type</b>	TKE/P 50
<b>Packing unit</b>	1
<b>ETIM-Classification</b>	EC000441

Description:

IP 68 Plastic cable gland. ESKV 50/ MFD 4 x 25 tails and 110-16mm earth. Kit contains insert, locknut and blanking insert.

Your Contact:

**WISKA UK Ltd.**

Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain

☎ +44-12-08816062 · 📠 +44-12-08816708



info@wiska.co.uk · www.wiska.co.uk

14.07.2019

Your Contact:

**WISKA UK Ltd.**

Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain

 +44-12-08816062 ·  +44-12-08816708

info@wiska.co.uk · www.wiska.co.uk