

INSULATION

Heatshrink Sleeves

HEATSHRINK SLEEVING

Cable Termination Components Heatshrink sleeving is available in Black, Clear, Blue, Brown, Grey, Yellow, White, Green, Red and Green/Yellow. Please specify which colour you require when ordering. We can supply on a roll or cut to length required. Our heatshrink has a continuous operating temperature of -55°C to 125°C and is flame retardant, UL Approved. Adhesive lined medium wall heatshrink and endcaps are also available ex stock.



HS SLEEVING LAYFLAT DIMENSIONS

HS Size	Dimensions (mm)
3.2	5
4.8	8
6.4	11
9.5	17
12.7	21
19	31
25	44
38	60
50	83
75	128
100	160

NB all dimensions stated are nominal

HEATSHRINK PACKS

Part Number	Length (mm)
HSP6	6.4 - 3.2
HSP9.5	9.5 - 4.7
HSP12	12.7 - 6.4
HSP19	19.1 - 9.5
HSP25	25.4 - 12.7
HSP38	38.1 - 19.0



HEATSHRINK BOXES

Available in Red, Yellow, Blue, Green/Yellow, Black, Grey, White, Clear and Brown.

Part Number	Box Quantity
HSB1.2	15m
HSB1.6	15m
HSB2.4	11m
HSB3.2	11m
HSB4.8	10m
HSB6.4	9m
HSB9.5	7m
HSB12	6m
HSB19	5m
HSB25	3.5m

HEATSHRINK GUNS

Part Number	Voltage
HSG110V	110V
HSG240V	240V

