



**Product Description:** 2W 3 Hour Non-Maintained Emergency Corridor Distribution


Includes LED driver and NiMH battery in a mesh sleeve. Compact downlight fits into a 40mm cut-out. LED module may also be mounted without downlight in a 20mm hole.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	SKU Type
EN-EMLD3	2	6000	132	66	150	Emergency

**Line Drawing**

**Polar Curve**

**Colour**



## Product Features:

- Non-maintained LED emergency train with corridor light distribution
- 2W High power LED
- Compact downlight fits into a 40mm cut-out
- 1 Year Warranty
- 3 Hour emergency duration
- Includes LED driver and NiMH battery in a mesh sleeve

## Product Specs:

Input Voltage	230~240V	Width (mm)	34
Length (mm)	1800	Overall Diameter (mm)	51
Weight (Kg)	0.329	Height (mm)	45
Product Type	Downlights, Emergency	Cutout Diameter (mm)	40-

## Compliance & Approvals:



## Warranty:

This product has a warranty period of 1 Year. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.