



Product Description: LEDLine™ PRO IP67 Single Colour Flexible Strip


LEDline™ PRO single colour 24V IP67 super bright LED strip is ideal for when LED strip with a higher lumen output is required in wet environments and external applications. Increased brightness by using twice as many LEDs per metre than standard LED strip. Low power consumption of 9.6W per metre. Strip can be cut to length and 2m leads soldered to special order.

| SKU Code | Wattage | Colour | Lumens | Lumens/Watt | Beam Angle | Finish Colour |
|--------------|---------|--------|--------|-------------|------------|---------------|
| EN-ST324/27 | 9.6 | 2700 | 800 | 84 | 120 | White |
| EN-ST324/30 | 9.6 | 3000 | 950 | 99 | 120 | White |
| EN-ST324/40 | 9.6 | 4000 | 988 | 103 | 120 | White |
| EN-ST324/60 | 9.6 | 6300 | 1036 | 108 | 120 | White |
| EN-ST324/BLU | 9.6 | | 227 | 24 | 120 | White |

Line Drawing

Polar Curve

Colour




Product Features:

- High density IP67 single colour flexible LED strip with 3M™ self adhesive backing
- Beam angle of 120° and 9mm between LEDs, 120 LEDs/m
- Cut points every 50mm for maximum flexibility
- Voltage drop of 4.5V per 5m and maximum run of 10m
- For runs over 10m lengths to be connected in parallel
- Any joints or termination points are maximum IP65 rated
- Requires 24V LED driver (sold separately)
- Reel length of 10m
- 3 year warranty

Product Specs:

| | | | |
|--------------------------|-----------|--------------------------|-----------|
| Input Voltage | 24~24V DC | IP Rating | IP67 |
| Lifetime L70 (hrs) | 35000 | Lamp Base | None |
| Width (mm) | 10 | Weight (Kg) | 0.619 |
| Height (mm) | 4 | Product Type | LED Strip |
| Operating Temp. (Min) °C | -20°C | Operating Temp. (Max) °C | 40°C |

Compliance & Approvals:



Warranty:

This product has a warranty period of 3 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.