















Product Description:

Poly-Slim™ 18W Round Polycarbonate Low Profile Downlight

Aurora's new range of Polycarbonate low profile downlights are engineered to deliver superior light output and uniformity utilising the latest edge-lit LED technology. At only 25mm deep including bracket, they are an ideal solution where ceiling voids are limited but high lumen output is required.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour	SKU Type
EN-PLPC18/40	18	4000	1650	92	120	Matt White	Non Dimmable
Line Drawing		Polar Cu	urve		Colour		
OD	↓				Matt White		

Product Features:

- Polycarbonate construction
- Delivering up to 92lm/W
- Edge-lit low profile ideal for installations in limited recess space (21mm) and shallow ceiling voids
- Supplied with remote nondimmable constant current LED driver (40mm void space required)
- 2 Year Warranty

Product Specs:

Input Voltage	220~240V AC
IP Rating	IP40
Overall Diameter (mm)	229
Height (mm)	21
Cutout Diameter (mm)	210-210
Operating Temp. (Max) °C	40°C

Power Factor	0.5		
Lifetime L70 (hrs)	15000		
Weight (Kg)	0.323		
Product Type	Downlights		
Operating Temp. (Min) °C	-20°C		

Compliance & Approvals:













Warranty

This product has a warranty period of 2 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.