




**Product Description:** mPro™ Adjustable IP65 Dimmable Fire Rated Downlight


Adjustable, integrated, fire rated 6W LED downlight with unique convertible design to fit ceiling voids as shallow as 56mm. Incorporated miniaturised NanoDrive™ power supply. Available in 3000K and 4000K, mPro™ delivers up to 107lm/W making it the most efficient fire rated downlight on the market. Interchangeable bezels available in White, Matt White, Polished Chrome and Satin Nickel. FastRFix™ rapid install system connector included for faster installation.  
PLEASE NOTE: Any purchases before 01/01/2021 has a 5 Year Warranty

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour	SKU Type
AU-MPRO2AMW/30	6	3000	610	102	60	Matt White	Triac Dimmable
AU-MPRO2AMW/40	6	4000	640	107	60	Matt White	Triac Dimmable
AU-MPRO2APC/40	6	4000	640	107	60	Polished Chrome	Triac Dimmable
AU-MPRO2ASN/30	6	3000	610	102	60	Satin Nickel	Triac Dimmable
AU-MPRO2ASN/40	6	4000	640	107	60	Satin Nickel	Triac Dimmable
AU-MPRO2AW/30	6	3000	610	102	60	White	Triac Dimmable
AU-MPRO2AW/40	6	4000	640	107	60	White	Triac Dimmable

## Line Drawing




## Polar Curve




## Colour




Matt White



Polished  
Chrome



Satin Nickel



White

## Product Features:

- LEDchroic™ lens provides halogen appearance with LED efficiency, anti-glare and precise beam control
- Convertible design to fit ceiling voids as shallow as 56mm
- Delivering up to 107lm/W
- IP65 rated
- FastRFix™ rapid install system connector included
- 60° beam angle for uniform light distribution
- Fibre based insulation coverable - up to 300mm
- Fire tested with solid timber, joist and metal web joists
- 7 Year Warranty
- PLEASE NOTE: When used with blown insulation, this product has a 5 Year Warranty at L70 40,000hrs
- PLEASE NOTE: Purchases before 2021 has a 5 Year Warranty

## Product Specs:

Input Voltage	220~240V AC	Input Frequency	50/50HZ
Power Factor	0.80	IP Rating	IP65
Lifetime L70 (hrs)	70000	Lifetime L80 (Hours)	70000L80B50
Overall Diameter (mm)	98	Weight (Kg)	0.529
Height (mm)	100	Product Type	Downlights, Fire-Rated Downlight
Cutout Diameter (mm)	85-85	Operating Temp. (Min) °C	-20°C
Operating Temp. (Max) °C	45°C		

## Compliance & Approvals:



## Warranty:

This product has a warranty period of 7 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.