

Luminaires | Floodlights

Aurora IP65 Proxima™ 50W 6000lm 4000K Floodlight

EN-FLP50/40



Photometrics

Wattage	50
Lumens	6000
Lm/W	120
Beam Angle	100
Colour Temperature	4000
Ra	80
SDCM	5
UGR19	No

Product Features

Brand	Aurora
IP Rating	IP65
IK Rating	IK08
L70 Hours	L80 50,000
Lifetime Class	L80
Dimmable	No
SKU Type	Non Dim
0-10V Dimming?	No

DALI Dimming?	No
1-10V Dimming?	No
DALI-2 Dimming?	No
DMX Dimming?	No
DSI Dimming?	No
Warranty	5 Years
Onsite Warranty	3 Year
Country of Origin	CN

Electrical Specification

Input Voltage (Min)	100
Input Voltage (Max)	277
Input Voltage Type	AC
Power Factor	0.9
Surge Protection (kV)	2
Protection Class	Class 1
Frequency (Min) Hz.	50
Frequency (Max) Hz.	60
Operating Temp. (Min) °C	-20
Operating Temp. (Max) °C	40
Glow Wire Test (°C)	650

Physical Attributes

Width (mm)	195
Height (mm)	153
Product Weight (KG)	1.098
Gross Weight - Product & Box (KG)	1.185
Material	Aluminium
Optic Material	Tempered Glass
Mount Options	Surface Mount
Packaging Length (mm)	225
Packaging Width (mm)	52

Packaging Height (mm)	182
Outer Packaging Length (Inches)	8.84
Outer Packaging Width (Inches)	9.24
Outer Packaging Height (Inches)	8.06
Barcode	5056100000000
Finish Colour	Black