## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: LUTEC

Supplier's address: LUTEC EUROPE NV, Herentalsebaan 425, 2160 Wommelgem, BE

## Model identifier: 5288902118M

## Type of light source:

| Lighting technology used:     | LED     | Non-directional or directional: | NDLS |  |  |  |
|-------------------------------|---------|---------------------------------|------|--|--|--|
| Light source cap-type         | Welding |                                 |      |  |  |  |
| (or other electric interface) |         |                                 |      |  |  |  |
| Mains or non-mains:           | MLS     | Connected light source (CLS):   | No   |  |  |  |
| Colour-tuneable light source: | No      | Envelope:                       | -    |  |  |  |
| High luminance light source:  | No      |                                 |      |  |  |  |
| Anti-glare shield:            | No      | Dimmable:                       | No   |  |  |  |
| Product parameters            |         |                                 |      |  |  |  |

| Product parameters   |  |                           |   |              |  |  |
|--|--|---------------------------|---|--------------|--|--|
| Parameter  |  | Value                     | Parameter   | Value        |  |  |
| General product parameters:  |  |                           |   |              |  |  |
| Energy consump<br>mode (kWh/1000<br>up to the nearest  | h), rounded                                  | 18                        | Energy efficiency<br>class  | E            |  |  |
| Useful luminous<br>indicating if it refe<br>in a sphere (360<br>cone (120 <sup>°</sup> ) or in a<br>(90 <sup>°</sup> ) | ers to the flux<br><sup>o</sup> ), in a wide | 1 950 in<br>Sphere (360°) | Correlated colour<br>temperature,<br>rounded to the<br>nearest 100 K,<br>or the range of<br>correlated colour<br>temperatures,<br>rounded to the<br>nearest 100 K, that<br>can be set | 4 000        |  |  |
| On-mode pov<br>expressed in W  | wer (P <sub>on</sub> ),                      | 17,3                      | Standby power (P <sub>sb</sub> ),<br>expressed in W<br>and rounded to the<br>second decimal   | 0,00         |  |  |
| Networked standb<br>for CLS, expresse<br>rounded to the se   | ed in W and                                  | -                         | Colour rendering<br>index, rounded to<br>the nearest integer,<br>or the range of CRI-<br>values that can be<br>set  | 80           |  |  |
| Outer H  | leight                                       | 15                        | Spectral power  | See image    |  |  |
| dimensions V   | Vidth  | 70                        | distribution in the   | in last page |  |  |
| without C  | Depth  | 227                       | -   |              |  |  |
| I  |  | 1                         | 1   | Page 1 /     |  |  |

| separate<br>control gear,<br>lighting<br>control parts<br>and non-<br>lighting<br>control parts,<br>if any<br>(millimetre)       |      | range 250 nm to 800<br>nm, at full-load  |                |  |  |  |
|--|------|--|----------------|--|--|--|
| Claim of equivalent power <sup>(a)</sup>   | Yes  | If yes, equivalent power (W)             | 123            |  |  |  |
|  |      | Chromaticity<br>coordinates (x and y)    | 0,380<br>0,380 |  |  |  |
| Parameters for LED and OLED light sources:   |      |  |                |  |  |  |
| R9 colour rendering index value  | 14   | Survival factor                          | 1,00           |  |  |  |
| the lumen maintenance factor   | 0,96 |  |                |  |  |  |
| Parameters for LED and OLED mains light sources:   |      |  |                |  |  |  |
| displacement factor (cos φ1)   | 0,70 | Colour consistency<br>in McAdam ellipses | 6              |  |  |  |
| Claims that an LED light<br>source replaces a fluorescent<br>light source without integrated<br>ballast of a particular wattage. | _(b) | lf yes then<br>replacement claim<br>(W)  | -              |  |  |  |
| Flicker metric (Pst LM)  | 1,0  | Stroboscopic effect<br>metric (SVM)      | 1,0            |  |  |  |

(a)'-' : not applicable;

(b)'\_-' : not applicable;

