Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: LUTEC
Supplier's address: LUTEC EUROPE NV. Herentalsebaan 425, 2160 Wommelgem,

Model identifier:	63/8102112M
iviouei identinei.	0.540 102 11210

_	•			
Type	Λt	liαht	COL	IIrco.
IVDE	VI.	IIGIIL	301	uice.

Type of light source:				
Lighting technology used:	LED	Non-directional or directional:	NDLS	
Light source cap-type	Welding			
(or other electric interface)				
Mains or non-mains:	MLS	Connected light source (CLS):	No	
Colour-tuneable light source:	No	Envelope:	-	
High luminance light source:	No			
Anti-glare shield:	No	Dimmable:	No	
Product parameters				
Parameter	Value	Parameter	Value	
General product parameters:				
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	8	Energy efficiency class	F	

Parameter		Value	Parameter	Value
		General product p	arameters:	
	mption in on- 100 h), rounded st integer	8	Energy efficiency class	F
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		750 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000
On-mode pexpressed in W	oower (P _{on}),	8,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer	Height	12	Spectral power	See image
dimensions	Width	150	distribution in the	in last page
without	Depth	156		Page 1 / 3

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)			range 250 nm to 800 nm, at full-load	
Claim of equivale	ent power ^(a)	Yes	If yes, equivalent power (W)	57
			Chromaticity	0,440
			coordinates (x and y)	0,403
Parameters for L	ED and OLED lig	ht sources:		
R9 colour render	ing index value	11	Survival factor	1,00
the lumen mainte	the lumen maintenance factor			
Parameters for LED and OLED mains light sources:				
displacement fac	tor (cos φ1)	0,70	Colour consistency in McAdam ellipses	6
source replaces light source with ballast of a partic	out integrated cular wattage.	_(b)	If yes then replacement claim (W)	-
Flicker metric (Ps	t LM)	1,0	Stroboscopic effect metric (SVM)	-

(a)_{'-'} : not applicable;

(b)_{'-'} : not applicable;

