Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: LUTEC

Supplier's address: LUTEC EUROPE NV, Herentalsebaan 425, 2160 Wommelgem, BE

Model identifier: 6382201012M

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	Welding		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
Energy consum mode (kWh/100 up to the neares	00 h), rounded	13	Energy efficiency class	E		
Useful luminou indicating if it re in a sphere (36 cone (120º) or in (90º)	efers to the flux 50°), in a wide	1 450 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000		
On-mode po expressed in W	ower (P _{on}),	13,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,00		
Networked stand for CLS, express rounded to the s	sed in W and	-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	80		
Outer	Height	15	Spectral power	See image		
dimensions	Width	113	distribution in the	in last page		
without	Depth	118				

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	96			
		Chromaticity coordinates (x and y)	0,440 0,403			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	13	Survival factor	1,00			
the lumen maintenance factor	0,96					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,70	Colour consistency in McAdam ellipses	6			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	lf yes then replacement claim (W)	-			
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	1,0			

(a)'-' : not applicable;

(b)'_-' : not applicable;

