## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light

sources	DELEGATED REGO	27 (20) 2013/20	ors with regard to ener	by labeling of light			
Supplier's nam	e or trade mark:	LUTEC					
Supplier's address: LUTEC EUROPE NV, Herentalsebaan 425, 2160 Wommelgem, BE							
Model identifie	er: 7199201118N	1					
Type of light so	ource:						
Lighting techno	ology used:	LED	Non-directional or directional:	NDLS			
Light source cap-type		Welding					
(or other electric interface)							
Mains or non-mains:		MLS	Connected light source (CLS):	No			
Colour-tuneable light source:		No	Envelope:	-			
High luminance light source:		No					
Anti-glare shield:		No	Dimmable:	No			
		Product para	meters				
Parameter		Value	Parameter	Value			
		General product p		ı			
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		13	Energy efficiency class	D			
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		1 690 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000			
On-mode power (P <sub>on</sub> ), expressed in W		12,5	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00			
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80			
Outer	Height	12	Spectral power	See image			
dimensions	Width	54	distribution in the	in last page			
without	Depth	54					

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)			range 250 nm to 800 nm, at full-load				
Claim of equivalent power <sup>(a)</sup>		Yes	If yes, equivalent power (W)	109			
			Chromaticity	0,440			
			coordinates (x and y)	0,403			
Parameters for LED and OLED light sources:							
R9 colour rendering index value		10	Survival factor	1,00			
the lumen maintenance factor		0,96					
Parameters for LED and OLED mains light sources:							
displacement factor (cos φ1)		0,70	Colour consistency in McAdam ellipses	6			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.		_(b)	If yes then replacement claim (W)	-			
Flicker metric (Pst LM)		1,0	Stroboscopic effect metric (SVM)	1,0			

(a)<sub>'-'</sub> : not applicable;

(b)<sub>'-'</sub> : not applicable;

