Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: LUTEC	
--------------------------------------	--

Supplier's address:	LUTEC EUROPE NV, Herentalsebaan 425, 2160 Wommelgem Wommelgem, BE
---------------------	---

Model	idontifior	7622104330M
IVIUUEI	iuciillei.	104330IVI

Tyne	οf	liσht	sourc	۵.
IVDE	UI.	HEIIL	Souit	┖.

LED	Non-directional or directional:	NDLS
Welding	3 2.2.2.2.3.4.	
MLS	Connected light source (CLS):	No
Yes	Envelope:	-
No		
No	Dimmable:	No
	Welding MLS Yes No	MLS Connected light source (CLS): Yes Envelope: No

Product parameters

Parameter		Value	Parameter	Value
	General product parameters:			
	mption in on- 100 h), rounded st integer	12	Energy efficiency class	Е
indicating if it r in a sphere (3	us flux (фuse), efers to the flux 60º), in a wide n a narrow cone	1 500 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	5 000
On-mode prespressed in W	oower (P _{on}),	12,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,45
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	80
Outer	Height	16	Spectral power	See image
dimensions	Width	60	distribution in the	in last page
without	Depth	70		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load	
Claim of equivalent power ^(a)	Yes	If yes, equivalent power (W)	99
		Chromaticity	0,346
		coordinates (x and y)	0,359
Parameters for LED and OLED I	ight sources:		
R9 colour rendering index value	16	Survival factor	1,00
the lumen maintenance factor	0,96		
Parameters for LED and OLED mains light sources:			
displacement factor (cos φ1)	0,70	Colour consistency in McAdam ellipses	6
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	:	If yes then replacement claim (W)	-
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	1,0

(a)'-': not applicable;

(b)_{'-'} : not applicable;

