# Ei1025



# Temperature, Humidity and CO2 Environmental Sensor



- Condensation, Damp, Mould and Indoor Air Quality
- Easy to install and manage
- Gather data on indoor environmental conditions
- Suitable for wall and ceiling mounting
- 10-year lithium battery
- Connection to Ei1000G SmartLINK Gateway required to extract data



## Description

The EilO25 temperature, humidity and CO2 environmental sensor is powered by a built in 10 year lithium battery. It connects wirelessly to the EilOOG SmartLINK Gateway to provide actionable insights on the health of a property via the HomeLINK Dashboard and Resident App, including risk of condensation, damp and mould, air quality, dust mite allergens, cold home risk and heat loss risk.

#### **Technical**

Sensor Type Temperature, Humidity and CO2 RF Frequency (MHz) 868.2

**RF Range (m)** >100 in free air **Battery Type** Lithium primary

**Technologies** HomeLINK

# **Dimensions & Weights**

 Depth (mm)
 34
 Height (mm)
 70

 Width (mm)
 70
 Product weight (kg)
 0.081

Packaged weight (kg) 0.134

### Approvals & Warranty

**Certification/Approvals**EN 300 220-1, EN 300 220-2, EN 301
489-1, EN 301 489-3 & EN 62368-1

Warranty
5 year warranty

WEEE Registration No.: WEE/AE0109WY Battery

**EAN Number** 5099383010183

### Environmental

Humidity Range (%) 15-95 Temperature Range (°C) -10 to 40

01691 664100 **E** enquiries@aico.co.uk **W** www.aico.co.uk

