Xnightsbridge


DATASHEET




RW6CCT

230V IP65 6W Fire-rated LED CCT Adjustable Downlight

www.mlaccessories.co.uk





MLA PART CODE	RW6CCT
DESCRIPTION	230V IP65 6W Fire-rated LED CCT Adjustable Downlight
NET WEIGHT (KG)	0.218
FINISH	White
DIFFUSER	Clear
DIMENSIONS (MM)	Diameter - 85 Projection - 7 Overall Height - 74 Recessed Depth - 67 Minimum Void - 120
CUT-OUT (MM)	Cut-out Diameter - 72
CONSTRUCTION	Construction - Aluminium Construction 2 - & polycarbonate
CLASS	I
IP RATING	IP65 (IP20 from above)
WATTAGE (W)	6
LAMP TECHNOLOGY	LED
LAMP INCLUDED	Yes
LUMENS (LM)	695
LUMENS LIGHT SOURCE ONLY (LM)	830
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	150.4
CIRCUIT WATTAGE (W)	5.56
ССТ	3000/4000/5000K
LIGHT COLOUR	ССТ
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.026
DISPLACEMENT FACTOR	>0.9
SVM	0.28
PST-LM	0.1





Xnightsbridge

BEAM ANGLE (DEGREES)	40
LIFE SPAN (HRS)	40,000
L70B50 LIFESPAN (HRS)	54,000
DIMMABLE	Yes*
FIRE-RATED	Tested to 30/60/90 minutes
IC RATED	Yes
OPERATING TEMPERATURE	35°C
INPUT VOLTAGE	230V 50Hz
DRIVER	EFFICIENCY FULL LOAD - 80.6
WARRANTY	5year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5055832981947

Date Created: 20/05/2022 14:32





