AURORA®
VALUE BEYOND ILLUMINATION™

EdgeLite™

Product Description: EdgeLite™ 1200mm x 300mm 36W Flat Panel

The EdgeLite™ has been upgraded to produce 95lm/W for outstanding energy savings. The light guide board and diffuser have been engineered to ensure maximum light output and complete uniformity. The range is TP(b) rated so suitable for a wide range of applications including office, education and commercial spaces.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour	SKU Type
EN-FP1230C/40	36	4000	3400	95	110	White	Non Dimmable
EN-FP1230C/50	36	5000	3400	95	110	White	Non Dimmable
EN-FP1230CDA/40	36	4000	3400	95	110	White	DALI Dimmable
EN-FP1230CDA/50	36	5000	3400	95	110	White	DALI Dimmable
EN-FP1230CV/40	36	4000	3400	95	110	White	1-10V Dimmable
EN-FP1230CV/50	36	5000	3400	95	110	White	1-10V Dimmable

Line Drawing



Polar Curve



Colour



White

Product Features:

- Edge-lit design and optical pattern light guide engineered for even light distribution
- Suitable for installation in 15 & 24mm T-bar ceilings
- RAL2016
- SDCM <5 providing consistent light colour quality
- TP(b) rated
- UGR 19 (Unified Glare Rating) - suitable for use in offices
- Flicker free driver - Power Factor >0.9
- Life not affected by frequent switching
- 1-10V dimmable, DALI and emergency versions available
- Surface mount box and adjustable suspension kit available
- 1.5kV surge protection
- 3 year warranty

Product Specs:

Input Voltage	220~240V AC	Input Frequency	50/60HZ
Power Factor	0.9	IP Rating	IP20
Lifetime L70 (hrs)	30000	Lamp Base	None
Width (mm)	295	Length (mm)	1195
Weight (Kg)	2.695	Height (mm)	10
Product Type	Panels	Operating Temp. (Min) °C	-20°C
Operating Temp. (Max) °C	40°C		

Compliance & Approvals:

Warranty:

This product has a warranty period of 3 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase.The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.