

**Part No:** C6TFH08-B204  
**Description:** The TruHD Cat 6 F/UTP Low Smoke Halogen Free (LSHF) cable has been tested and recommended by the HDBaseT Alliance making it the ideal choice for high speed data networks across a home or building.





### Construction

**Conductor** : Bare Copper  
**AWG** : 23(1)  
**Insulation Material** : High Density Polyethylene (HDPE)  
**Number of Pairs** : 4  
**Pair Identification** : Blue, Blue/White; Orange, Orange/White  
 : Green, Green/White; Brown, Brown/White  
**Drain Wire** : 0.40mm, Tinned Copper  
**Overall Screen** : Aluminium Foil (100% Coverage)  
**Outer Sheath Material** : Low Smoke Halogen Free (LSHF)  
**Outer Sheath Colour** : Orange



### Electrical Characteristics

**Max. Conductor Resistance @ 20°C** : ≤ 9.5 Ω/100m  
**Max. Resistance Unbalanced** : ≤ 2.0 %  
**Nominal Impedance (1-100MHz)** : 100 ± 5 Ω  
**Mutual Capacitance** : ≤ 56 pF/m  
**Capacitance Unbalanced** : ≤ 1600 pF/ km  
**NVP** : 68.5 % ± 2  
**Max. Delay Skew** : ≤ 45 nS/ 100m  
**Voltage Rating EN 50525-1** : 125V  
**Test Voltage** : 1kV

### Physical Characteristics

**Overall Diameter** : 7.1 ± 0.3mm  
**Bend Radius** : Fixed 4 x OD Flexing 8 x OD  
**Temperature Rating** : Fixed -20°C to 60°C Flexing 0°C to 50°C  
**Weight** : 65 kg/km

### Transmission Performance

Frequency	1	4	10	100	200	250	MHz
Attenuation	2.1	3.8	6.0	19.9	29.1	33.0	≤dB
Return Loss	34	30	27	20	18	17	≥dB
NEXT	75	66	60	45	41	39	≥dB
PS NEXT	72	63	57	42	38	36	≥dB
ACRF	68	56	48	28	22	20	≥dB
PS-ACRF	65	53	45	25	19	17	≥dB

### Standards

<b>Flame Retardant</b> : BS EN 60332-1-2	<b>Low Smoke Generation</b> : BS EN 61034-2
<b>Halogen Gas Emission</b> : BS EN 60754-1&2	<b>Approval</b> : HDBaseT
<b>RoHS3 Compliance</b> : Yes	<b>Manufactured in accordance to</b> : TIA/EIA 568-C.2, ISO/IEC 11801 Class E, EN 50288-5-1, ISO/IEC 61156-5
<b>CE Compliant</b> : LVD (2014/35/EU), CPR (305/2011)	<b>CPR Classification</b> : B2ca s1a, d1, a1 (EN50575:2014+A1:2016)