

Data sheet

ID **MAK WS**


Description maxi trunking

Properties Cable routing system for all kinds of electrical installations and telecommunication systems (telephone, EDP, TV, IT etc.) in residential and industrial buildings, offices, garages, hotels, schools and kindergartens; special clip-on system for robust connections between trunking body and lid (shock- and child-proof).

Colour white, similar to RAL 9010

Fire Behaviour non flame propagating

Norms: EN 50085, BS 4678 Part 4



Length	Number of covers	Number of plug-in partitions
3000 mm	1	2

Art. no.	Width x Depth	Useful cross section	Small Package	Large Package
036 996	50 x 50 mm	2500 mm ²	3 m	12 m
019 007	75 x 50 mm	3750 mm ²	3 m	12 m
036 997	100 x 50 mm	5000 mm ²	3 m	12 m
022 788	150 x 50 mm	7500 mm ²	3 m	6 m
019 008	75 x 75 mm	5625 mm ²	3 m	12 m
019 010	100 x 75 mm	7500 mm ²	3 m	6 m
022 953	150 x 75 mm	11250 mm ²	3 m	6 m
019 011	100 x 100 mm	10000 mm ²	3 m	6 m
022 789	150 x 100 mm	15000 mm ²	3 m	84 m
022 790	150 x 150 mm	22500 mm ²	3 m	60 m

Further technical details

Details

Covers supplied with the product True

Symmetric True

Construction type rectangular True

Halogen free False

Surface protection Untreated

Construction rear wall (inner side) Continuous C-profile

Protection film False

With duct connector False

Mounting perforation in base False

Mounting method covers Spanned

With cable fixing clip False

Material PVC-U