

DATASHEET



OS009

IP20 360° PIR Sensor - Recess Mounting

www.mlaccessories.co.uk

MLA PART CODE	OS009
DESCRIPTION	IP20 360° PIR Sensor - Recess Mounting
NET WEIGHT (KG)	0.083
FINISH	White
DIMENSIONS (MM)	Diameter - 76 Recessed Depth - 58
CUT-OUT (MM)	Cut-out Diameter - 62
CONSTRUCTION	Construction - Polycarbonate
CLASS	II
IP RATING	IP20
IC RATED	No
OPERATING TEMPERATURE	-20 to 40°C
INPUT VOLTAGE	230V 50Hz
LOAD/MAX. LOAD	1200W Incandescent / 300W LED
ADDITIONAL FEATURES	Optimum installation height 2.2 to 4m
FUNCTION	Adjustable Lux, Adjustable Time
SENSOR TYPE	PIR
SENSOR OVERRIDE	No
SENSOR DETECTION ANGLE (DEGREES)	360
OPTIMUM DETECTION RANGE (M)	6 @ 2.4m height
SENSOR DURATION	10 seconds to 8 minutes
SENSOR LUX SETTINGS	3 - 2000 lux
STANDBY POWER	0.1W
WARRANTY	1year(s)
MANUFACTURED IN ACCORDANCE WITH	EN 60669-2, EN 60669-1
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5055832930419

Date Created: 02/08/2022 17:08