

















Product Description:

Vela™ 50W Adjustable IP65 Driverless Floodlight

The IP65 driverless range of VelaTM floodlights comes complete with an ultra slim profile and high performance. Delivering 120Im/W and with the product being salt spray tested, it offers a solution for coastal applications.

SKU Code	Wattage	Colour	Lumens	Lumens/Watt	Beam Angle	Finish Colour	SKU Type
EN-FLV50/40	50	4000	6000	120	110	Black	Non Dimmable
Line Drawing	Line Drawing Polar Cui		urve		Colour		
. 4		150" 150"	150"			_	







Product Features:

Tempered frosted glass

- Aluminium housing for excellent IP65 rated heat dissipation

 - IK06 rated

- Salt spray tested and approved
- Pre-wired with 800mm of cableL70 30,000hrs
- 3 Year Warranty

Product Specs:

Input Voltage	220~240V AC
Power Factor	0.9
Lifetime L70 (hrs)	30000
Width (mm)	196
Product Type	Floodlights
Operating Temp. (Max) °C	45°C

Inp	ut Frequency	50/60HZ
IP I	Rating	IP65
IK I	Rating	IK06
Hei	ight (mm)	143
Ор	erating Temp. (Min) °C	-35°C

Compliance & Approvals:

This product has a warranty period of 3 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.