




Product Description: ReflectCS™ 25W IP54 Colour Switchable Downlight

The ReflectCS™ range is a colour switchable downlight with a high powered SMD. Featuring a sparkling multifaceted aluminium reflector designed for exceptional light control and providing a 60 degree beam angle for focused downlighting. The downlight can be switchable between 3000K (2520 lumens), 4000K (2665 lumens) and 5700K (2604 lumens).

With this versatile downlight, by making your colour selection prior to install it makes it ideal for various applications. Please note: lumen value in SKU table is stated at 4000K.


SKU Code	Wattage	ColorTemp	Lumens	BeamAngle	SKUType	FinishColor
EN-DDL258CCT	25	3000K	2520	60	Triac Dimmable	White
EN-DDL258CCT	25	4000K	2665	60	Triac Dimmable	White
EN-DDL258CCT	25	5700K	2604	60	Triac Dimmable	White
EN-DDL258CCTDA	25	3000K	3390	60	DALI Dimmable	White
EN-DDL258CCTDA	25	4000K	3600	60	DALI Dimmable	White
EN-DDL258CCTDA	25	5700K	3400	60	DALI Dimmable	White
EN-DDL258CCTV	25	3000K	3390	60	1-10V Dimmable	White
EN-DDL258CCTV	25	4000K	3600	60	1-10V Dimmable	White
EN-DDL258CCTV	25	5700K	3400	60	1-10V Dimmable	White

Line Drawing



Polar Curve

Colour



White

Product Features:

- Colour switchable between 3000K, 4000K & 5700K
- High powered SMD with a multifaceted aluminium reflector
- Delivering up to 107lm/W (at 4000K)
- Lumen Value at 3000K - 2520lm
- Lumen Value at 4000K - 2665lm
- Lumen Value at 5700K - 2604lm
- 60° beam angle
- IP54 rated
- Supplied with remote triac dimmable constant current driver
- 5 Year Warranty

Product Specs:

Input Voltage	200~240V AC	Power Factor	0.9
IP Rating	IP54	Lifetime L70 (hrs)	50000
Overall Diameter (mm)	235	Weight (Kg)	0.598
Height (mm)	100	Product Type	Downlights
Cutout Diameter (mm)	200-210	Operating Temp. (Min) °C	-20°C
Operating Temp. (Max) °C	40°C		

Compliance & Approvals:



Warranty:

This product has a warranty period of 5 Years. Warranties may be available on certain products as indicated in the product description. Warranties are valid from the date of purchase. The warranty is invalid in the case of improper use, installation, tampering, removal of the Q.C. date label or installation in an improper working environment or installation. Should this product fail during the warranty period it will be replaced free of charge, subject to the correct installation of the original product and subsequent return of the faulty unit. Aurora does not accept responsibility for any installation costs associated with the replacement of this product and Aurora reserves the right to alter specifications without prior notice.