Data sheet | Item number: 207-1331

Gelbox; for cables; Branch; with gel; 221, 2x73 Series; max. 4 mm² connectors; without splicing connectors; Size 1; gray









Note on Packaging Unit (PU) and Subpackaging Unit (SPU):

If you order a full PU, you will receive our eco-friendly, sustainable cardboard blisters packed in a shelf-ready box. If you order a quantity smaller than a full PU, you will receive the eco-friendly, sustainable cardboard blisters without a shelf-ready box.

Please refer to the system description for the splicing connectors that can be used.

Your benefits:

- Easy, fast and safe to use
- · Can be used immediately and accessed again later
- · Silicon-free
- Label-free
- · Suitable for indefinite storage
- The complete system consisting of WAGO's gelboxes and splicing connectors has been VDE-tested and IPX8-certified.

Connection data Connection 1 Actuation type Locking system

Physical data	
Width	33.6 mm / 1.323 inches
Height	17.8 mm / 0.701 inches
Depth	32 mm / 1.26 inches

Mechanical data	
Mounting type	Flying leads

Data sheet | Item number: 207-1331

https://www.wago.com/207-1331



Material data	
Note (material data)	Information on material data can be found here
Color	gray
Housing material	Polypropylene
Fire load	0 MJ
Weight	12 g

Environmental requirements	
Ambient temperature (operation)	-55 +85 ℃
Surrounding air temperature (storage)	0+40°C

 $\label{thm:condition} \textbf{Subject to changes. Please also observe the further product documentation!}$

Current addresses can be found at: $\underline{www.wago.com}$

Page 2/2 Version 16.10.2022