





Model. SF100

100A Switch Fuse TPN Grey Steel Enclosure

Features & Benefits

- Supplied with installation instructions and suitable for use with 250v
- Fuses fully isolated (top & bottom) for safe replacement
- · Highest available components to current specifications and supplied with switch fuses
- Complies to low voltage directive 73/23/EEC and takes BS88 Part 2 Fuses
- Rust protected epoxy grey powder paint finish with adequate knockouts on each side and lockable handle
 Ceramic Terminal Fuse Base with 415v 50Hz Triple Pole and Neutral (4 Poles)

Safety Information

IMPORTANT - Before undertaking any work on or maintenance of fitting:-

- Switch off power supply and allow sufficient time to cool before handling
 Do not dispose of decommissioned fitting in household waste
- Dispose of fitting in the appropriate section of your local civic amenity site or recycling centre only

Technical Specifications

General Information	
Product Colour/Finish	Dark Metallic Grey
Dimensions (mm)	400x273x245mm
Ingress Protection (IP)	IP41
Electrical	
Load (Amp)	100Amp
Rated voltage/amps (vA)	440vA
Terminal Capacity (mm ²)	70mm ²
Input Voltage (v)	415v - 50Hz
Output Voltage (v)	440V
Knock Outs (mm)	2x25 1x32
Cable Length (Mtrs)	1.6mm
Poles	TPN
Approvals/Certifications	CE
Construction	
Body Material	Steel Enclosure
Weight (g)	1250g
Warranty Period (Years)	1Yr
Other	
Applications	Suitable for demostic, commercial and Industrial applications

Applications

Suitable for domestic, commercial and Industrial applications

