


## SH0425/W

### SHARK T Branch



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.

<b>Material</b>	Polyamide
<b>Filling</b>	Silicone
<b>Temp. range min</b>	-20 °C
<b>Temp. range max</b>	90 °C
<b>Glow wire test</b>	self-extinguishing
<b>Voltage</b>	0,6 kV - 1 kV
<b>Quantity of cable</b>	1
<b>Type</b>	SH0425/W
<b>UK-Number</b>	10111406
<b>WISKA-Order no.</b>	10111406
<b>Packing unit</b>	1
<b>ETIM-Classification</b>	EC001169

#### Remarks:

Cable Size: Main Cable up to 150 mm Branch cable up to 50 mm

LxBxH: 210x125x49 mm

#### Description:

SHARK T BRANCH Pre-filled gel insulated T joint for branch connection.

#### Additional Info:

Ready to use, re-enterable, no mixing or pouring, immediate operation, excellent electrical insulation, good mechanical strenght, no expiry date.

05.04.2023


#### Your Contact:

**WISKA UK Ltd.**

Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain

☎ +44-12-08816062 · 📠 +44-12-08816708

info@wiska.co.uk · www.wiska.co.uk



Your Contact:

**WISKA UK Ltd.**

Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain

☎ +44-12-08816062 · 📠 +44-12-08816708

info@wiska.co.uk · www.wiska.co.uk

Other technical data on request / subject to change without notice