



WPSS82W-USB

IP20

13A 2 Gang Double Pole Switched Socket c/w Twin USB White

Technical characteristics

Architecture

| | |
|-------------|----------------|
| Fixing mode | flush-mounting |
|-------------|----------------|

Main electrical features

| | |
|-----------------|----------------|
| Nominal voltage | 250 V |
| Rated voltage | 220...230 V AC |

Dimensions

| | |
|--------|---------|
| Depth | 53.2 mm |
| Height | 86 mm |
| Width | 146 mm |

Cover, door

| | |
|-------|------------------|
| Cover | Full cover plate |
|-------|------------------|

Materials

| | |
|---------------------------|-------|
| Colour | white |
| Material | Steel |
| Type of surface treatment | Epoxy |

Connection

| | |
|--------------------|-------|
| Type of connection | screw |
|--------------------|-------|

Cable

| | |
|--------|------------------------------|
| Wiring | with double earth connection |
|--------|------------------------------|

Scope of delivery

| | |
|-----------|---|
| Component | with 2 fixing screws M3.5 x 20 mm and M3.5 x 30 mm each |
|-----------|---|

Safety

| | |
|---------------------|-----------------------------|
| Protection index IP | IP20 |
| Protection | Enhanced contact protection |