

**EXTRA** 

**FLAT** 

## LOOX5 12V DRIVERS

The driver is the heart of the Loox system, and is suitable for connecting to all of the world's power systems. Driver includes one output - a distributor is required for multiple lights. Optional Bluetooth® distributor also available for control via App.

## Loox5 12V LED driver, constant voltage



- > With twin overload protection
- > Input voltage: 220-240V for 20W driver, 100-240V for 40/60W drivers; 50-60Hz
- > Output voltage: DC 12V
- > Number of connections: 1x socket Loox5 12V
- > Lifetime: >50,000 hours
- > Standby power consumption W: ≤ 0.8W for 20W driver, ≤ 0.12W for 40W driver, ≤ 0.14W for 60W drive
- > Degree of protection: IP20
- > Ambient temperature -25°C to +45°C (60W: 40 °C)
- > Supplied with: 1x driver with mounting accessories
- > Black plastic
- > Order qty: 1 pc

ARTICLE REMOVED FROM PAGE 833.95.000 Replaced by new number 833.95.001















- > Loox mains leads must be ordered separately, shown below
  - > Distributor must be ordered separately for
  - more than one light, shown on page 5.158











Length x width x height	Output power	Output current	Cat. No.
140 x 50 x 16 mm	20W	1.67A	833.95.001
191 x 60 x 16 mm	40W	3.33A	833.95.002
230 x 70 x 16 mm	60W	5.00A	833.95.003



- > Provide for sufficient air supply and circulation at the mounting location of the driver; we recommend 10 mm clearance
- Maximum lead length from the Loox5 driver to the light is 10 m. Long cable lengths in combination with large loads (strip light lengths) can result in voltage losses in the cable. These lead to visible loss of brightness in the lights. The illuminance listed with the lights has been determined with the rated output voltage of the driver (12V or 24V).

## Loox mains leads, C7



- > Voltage: 250V
- > Length: 2000 or 5000 mm
- > Black plastic
- > Order qty: 1 pc



Country specific mains leads are available more info on request

Туре	Voltage	2000 mm	5000 mm	
Moulded plug	250V	833.89.000	833.89.080	
Bare ended	250V	833.89.009	-	



