


Häfele Connect Mesh Eco distributor, monochrome, 4-way, with switching function



- > For on/off switching and dimming (0-100%) of monochromatic lights
- > Use the remote control to select one of the four outputs (output 1, 2, 3 or 4) and simultaneously control this output to all distributors of the network (on/off, dimming level).
- > Distributor: Dim. (L X W X H): 105 x 50 x 16 mm
- > Remote control: Dim. (L X W X H): 125 x 40 x 12 m
- > Number of connections:
 - 1x input port with box to box plug
 - 1x output port with box to box socket
 - 4x output ports consumer sockets
- > Supplied with: 1x 4-way distributor, monochrome, 1x remote control
- > Black plastic
- > Order qty: 1 pc





The distance between the smartphone or tablet to the nearest Häfele Connect Mesh component is approx. 10 m. Multiple components create a network, and can be placed approx 10 m apart.








Voltage	Memory function	Power rating	Cat. No.	
12V	No	36W	850.00.981	
24V	Yes	72W	850.00.982	

Häfele Connect Mesh Eco distributor, multi-white, 4-way, with switching function



- > For on/off switching and dimming (0-100%) of multi-white lights
- > Use the remote control to select one of the four outputs (output 1, 2, 3 or 4) and simultaneously control this output to all distributors of the network (on/off, dimming level).
- > Distributor: Dim. (L X W X H): 105 x 50 x 16 mm
- > Remote control: Dim. (L X W X H): 125 x 40 x 12 m
- Number of connections:
 - 1x input port with box to box plug
- 1x output port with box to box socket
- 4x output ports consumer sockets
- > Supplied with: 1x 4-way distributor, multi-white, 1x remote control
- > Black plastic
- > Order qty: 1 pc





ICH DESIGN 2020, © Häfele U.K. Ltd 2020. Dimensional data not binding. We reserve the right to alter specifications without notice

The distance between the smartphone or tablet to the nearest Häfele Connect Mesh component is approx. 10 m. Multiple components create a network, and can be placed approx 10 m apart.







Voltage	Memory function	Power rating	Cat. No.	
12V	No	36W	850.00.983	
24V	Yes	72W	850.00.984	