

103850

Microwave Sensor IP65

FEATURES

- 5 years (2 years + 3 years) extended warranty
- Frosted & white ABS plastic finish
- Constructed from ABS plastic
- Complete with built in photocell & PIR
- 10 lux On, 50 lux Off. 150° detection angle, 6m maximum range with a 5 second to 30 min timer function
- IP65

SPEC DATA

Voltage:	220-240V 50Hz a.c.
Load:	400W (inductive), 800W (resistive)
HF System:	5.8GHz±75MHz, ISM wave band
Transmitting Power:	<0.5mW
Power Consumption:	≤0.5W (standby)
Detection zone:	Max. (D x H): 12m x 10m
Detection sensitivity:	25% / 50% / 75% / 100%
Hold Time:	5s / 30s / 1min / 3mins / 20mins / 30 mins
Daylight sensor:	2Lux / 10Lux / 25Lux / 50Lux / 100Lux / Disable
Daylight open/close:	10Lux / 50Lux; 25Lux / 75Lux; 50Lux / 100Lux; 100Lux / 200Lux; 150Lux / 300 Lux; Disable.
Mounting height:	6m Max.
Motion detection:	0.5~3m/s
Detection angle:	150° (wall installation) / 360° (ceiling installation)
Operating temperature:	-25°C to +60°C

