

77898

Forca CCT Microwave

FEATURES

- 5 years (2 years + 3 years) extended warranty
- Gloss white & opal PC finish
- Constructed from polycarbonate
- Complete with built in microwave sensor
- IP65
- IK08
- BESA installation
- 4-side knockouts
- Interchangeable bezels

SPEC DATA

| | |
|------------------------|------------------------|
| Product Wattage: | 18W |
| Product Lumen: | 1600 |
| Lumen/W: | 89 |
| Kelvin: | 3000/4000/6500K |
| Energy Rating: | A+ |
| Dimmable: | No |
| Beam Angle: | 120° |
| Power Factor: | 0.9 |
| CRI: | 80 |
| Lifetime (Hours): | 35000 |
| LED Brand: | Epistar |
| SDCM: | <6 |
| Driver Type: | Constant Current 260mA |
| Product Voltage: | 220-240V |
| Hertz: | 50/60 |
| Surge Protection (KV): | 3.7 |
| Operating Temp.: | -20 to 45 Degree |
| Product Weight (KG): | 0.785 |
| Terminal Block: | 2-way fast fix |
| Class: | 2 |

MICROWAVE MOVEMENT SENSOR DATA

| | |
|----------------------|--|
| Operating Voltage: | 220 ~ 240Vac |
| Hertz: | 50/60 |
| Rated Load: | 400W (Capacitive load) 800W (Resistive load) |
| Stand-by Power: | ≤ 0.5W |
| Sensitivity: | Ceiling Height 3m: 100% / 75% / 50% / 25% / 10% Ceiling Height 6m: 100% / 75% / 50% Wall Height 2m: 100% / 75% / 50% / 25% / 10% |
| Hold-time: | 5s / 30s / 90s / 3min / 20min / 30min |
| Daylight Sensor: | 2Lux / 10Lux / 25Lux / 50Lux / Disable |
| Microwave Frequency: | 5.8 GHz ± 75MHz |
| Transmitting Power: | 1mW Max. |
| Detection Range: | Ceiling Height 3m: 3-6m (radius) Wall Height 1.5-2m: 12-15m |
| Detection Angle: | 360° (Ceiling) / 120° (Wall) |
| Working Temperature: | -20°C ~ 60°C |

ACCESSORIES

| | |
|---------------------------------|------------------------------------|
| 77904, Forca white plain bezel | 77910, Forca black plain bezel |
| 77905, Forca white eyelid bezel | 77911, Forca black eyelid bezel |
| 77907, Forca grey plain bezel | 77912, Forca black grill bezel |
| 77908, Forca grey eyelid bezel | 77913, Forca chrome plain bezel |
| 77909, Forca grey grill bezel | 78286, Forca anti-theft screw pack |

