

**EVOFIRE MINI FIRE RATED DOWNLIGHT 45MM CUTOUT IP65 ANTIQUE BRASS ROUND INTEGRAL**

ILDLFR45D041



Ideal for new builds - Only a 45mm cut-out (for MR11 12V GU4 or MR11 240V GU10 lamps). Great for tight spaces - 38.5mm super-low profile. Aesthetic - Ultra-thin 1mm blend-in bezel with a premium finish. Easy wiring - with a Fast-Fit, loop-in/loop-out, junction box for tool free assembly. Easy to install and remove - Durable steel assembly. Extended lamp life - Open design allows airflow to extend lamp life compared to traditional designs. 45mm Cut-Out, 64mm Diameter, IP65. This downlight is fire rated to 30, 60 and 90 minutes in compliance with BS476 Part 21:1987, Air Tightness compliant with Part C and Part L and Resistance to Sound compliant with Part E. See installation guide for full details.

**Details**

|                             |                                       |
|-----------------------------|---------------------------------------|
| <b>Quick Order Code:</b>    | 082018                                |
| <b>Barcode:</b>             | 5055788267775                         |
| <b>Category:</b>            | Downlights                            |
| <b>Range Name:</b>          | EvoFire mini                          |
| <b>Product Body Finish:</b> | Antique Brass                         |
| <b>Market Segment:</b>      | Commercial indoor, Residential indoor |
| <b>Finish:</b>              | Antique Brass                         |
| <b>Warranty (Years):</b>    | 3                                     |
| <b>CE RoHS:</b>             | Yes                                   |

**Physical Data**

|                                 |                          |
|---------------------------------|--------------------------|
| <b>Product Depth (mm):</b>      | 38.5                     |
| <b>Product Weight (g):</b>      | 10                       |
| <b>Material:</b>                | Steel, Glass             |
| <b>Overall diameter (mm):</b>   | 64                       |
| <b>Construction:</b>            | Pressed Steel, Glass     |
| <b>Cut Out Diameter (mm):</b>   | 45                       |
| <b>Luminaire Fixing:</b>        | Recess mounted           |
| <b>Placement / Application:</b> | Indoor, General Lighting |

**Electrical Data**
**Light Data**

|                            |            |
|----------------------------|------------|
| <b>Fire Rating (mins):</b> | 30, 60, 90 |
|----------------------------|------------|

## Environment

|                                 |      |
|---------------------------------|------|
| CE RoHS:                        | Yes  |
| IP Rating (Back/Recessed side): | IP20 |
| IP Rating (Ingress Protection): | IP65 |

## Packaging

|                      |      |
|----------------------|------|
| Package Weight (g):  | 13   |
| Package Length (mm): | 70   |
| Package Width (mm):  | 70   |
| Package Depth (mm):  | 65   |
| Qty per euro pallet: | 1632 |