

SY2-C40XLED Data Sheet

Type 2/3 SPD

SURge
PROTECTION DEVICES LTD



- Compliant to BS EN 61643-11
- Suitable for TNC-S, TN-S and TT installations
- LED Indication
- Pluggable replacement modules
- Remote changeover contacts as standard
- Din rail mountable
- Recommended backup fuse / MCB 32A
- Recommended cable size minimum 6mm



SCAN THE QR CODE FOR THE
**INSTALLATION
INSTRUCTIONS**



Device Configurations

SY2-C40XLED/ENC

SY2-C40XLED
Complete in
IP Enclosure

SY2-C40XLED/ENCM

SY2-C40XLED
Complete in
IP Enclosure
With 32A MCB

SY2-C40XLED/ENCMET

SY2-C40XLED
Complete in
Metal Enclosure

SY2-C40XLED/ENCMETM

SY2-C40XLED
Complete in
Metal Enclosure
With 32A MCB

Technical Data	SY2-C40XLED
Maximum Continuous Voltage - U_c	275V
Nominal Discharge Current 8/20 μ s - I_n	20kA
Maximum Discharge Current 8/20 μ s - I_{max}	40kA
Voltage Protection Level - U_p @ I_n	≤ 1.4 kV
Voltage Protection Level - U_p @ 5kA	≤ 1.00 kV
Response Time - t_a	≤ 25 ns
Tightening Torque	3Nm
Operating Temperature	-40°C to +80°C
Dimensions	4 Modules
Mounting On	35mm DIN rail
Indication of Status	LED & Remote
Classification According to BS EN 61643-11	Type 2/3

01484 851747

info@surgedevices.co.uk

