

LOOX 12V LED 2022 DOWNLIGHT


When recess mounted the LED 2022 downlight has an IP rating of 44, making it ideal for bathrooms or other zone 1 areas. Can also be surface mounted when installed using optional bezels, round or wedge shaped.



5

Lighting: Loox LED

Loox 12V LED 2022 downlight, Ø 35 mm, IP44 rated



- > 1.5 mm rim, min. 13 mm hole depth required
- > For recess mounting, press-fit in Ø 26 mm hole
- > Voltage: 12V. Wattage: 1.5W
- > Dimmable
- > Degree of protection:
 - IP44 as recess mounted downlight
 - IP20 as surface mounted downlight with bezel
- > With 2.0 m lead with Loox 12V connector
- > Aluminium housing
- > Order qty: 1 pc

Output:	3000 K	4000 K	5000 K
Light colour:	Warm white	Cool white	Cool white
Wattage (W):	1.5	1.5	1.5
Energy efficiency:	A+ G	A+ G	A+ G
Number of diodes	3	3	3
Light output (Lm):	105	105	105
Efficacy (Lm/W):	70	70	70
Colour Rendering Index:	82	87	88

Distance	90°	3000 K	4000 K	5000 K
250 mm		650 Lx	650 Lx	650 Lx
500 mm		163 Lx	163 Lx	163 Lx
750 mm		72 Lx	72 Lx	72 Lx
1000 mm		40 Lx	40 Lx	40 Lx

12V

+ Order bezels separately for surface mounting, shown on page 5.31

Finish	3000 K	4000 K	5000 K
Chrome-plated polished	833.72.043	833.72.044	833.72.045
Silver coloured anodised	833.72.040	833.72.041	833.72.042

YOU ALSO NEED:

DRIVER
Page 5.74

SWITCH
Page 5.79-86

OPTIONAL ACCESSORIES
Pages 5.75, 5.78

PAGE AMENDED
19.05.22/1