

Ei660i

Multi-Sensor Fire Alarm



- Contains both an Optical and Heat sensor for a total fire response
- 10 year Lithium battery powered
- Built in AudioLINK+ data extraction technology
- Kitemarked to BS EN14604:2005 & BS5446-2:2003
- 5 year guarantee



Description

The Ei660i is a battery powered Multi-Sensor Fire Alarm that contains a sealed in, tamper proof lithium battery that will last for the full 10 year life of the alarm. It contains built-in AudioLINK+ data extraction technology and features a large test button and twist on base with an anti-tamper locking option

General Information

Battery Type	Lithium primary	Battery weight (kg)	0.017
Depth (mm)	120	Fixings	Screws included
Humidity Range (%)	15-95	Indicators	Red - Alarm, fault
Kitemark reference	KM 83678 & KM 522831	Luckins TSI Code	434833856
Material	HIP UL94 V0 Flame retardant	Outer paper/cardboard weight (kg)	0.022
Packaged weight (kg)	0.228	Paper/cardboard weight (kg)	0.012
Sensor Type	Optical and Heat (AI) - with dust compensation	Plastic weight (kg)	0
Technologies	AudioLINK+	Product weight (kg)	0.196
Temperature Range (°C)	-10 to 40	Warranty	5 year warranty
Width (mm)	120		

Technical

Sensor Type	Optical and Heat (AI) - with dust compensation	Indicators	Red - Alarm, fault
Battery Type	Lithium primary	Technologies	AudioLINK+

Dimensions & Weights



Depth (mm) 120
Width (mm) 120
Packaged weight (kg) 0.228

Height (mm) 59
Product weight (kg) 0.196

Approvals & Warranty

Certification/Approvals EN 14604: 2005, BS 5446-2:2003
EAN Number 5099383010350

Warranty 5 year warranty

Environmental

Humidity Range (%) 15-95

Temperature Range (°C) -10 to 40

T 01691 664100 **E** enquiries@aico.co.uk **W** www.aico.co.uk

Company Registration No.: 2544399
Producer Registration No.: BPRN00307

WEEE Registration No.: WEE/AE0109WY Battery

an  Company