PRODUCT DATA SHEET

Aurora AU-BH115CS

Aurora IP65 Utilite™CS 15W Upto 1650lm 3000K/4000K/6500K Round Utility Bulkhead


Manufacturer: Aurora Lighting UK

GTIN: 5056102052343

Family: Luminaires

Range: Bulkheads





DESCRIPTION

Utilite™CS round bulkhead has impact resistant polycarbonate housing, providing a tough exterior and making them ideal for all basic industrial, commercial and residential installations. Separate eyelid and grille bezels are available. The range also features colour switchable technology allowing the colour temperature to be set at either 3000K. 4000K or 6500K on site.

- Colour switchable between 3000K/4000K/6500K
- Polycarbonate body and diffuser
- IP65 rated
- IK06 rated
- -20° - +40° ambient operating temperature
- 3 Year Warranty

TECHNICAL SPECIFICATION

ETIM Class: Ceiling / wall luminaire (EC002892)

Primary Features

Colour of light	White	Light source included	No
Colour temperature (K)	3000 - 6500	Light source type	Other
Housing colour	White	Maximum system power (W)	15
Lamp cap/base	Other	Nominal voltage (V)	240 - 240
Lamp power (W)	15 - 15	Voltage type	AC

Additional Features

Beam angle	Extreme wide beam >80°	Light outlet	Direct
Beam angle adjustable	No	Lumen setting adjustable	Distinct positions
Colour consistency (McAdam ellipse)	SDCM6	Luminaire may be covered with thermally insulating material	No
Colour rendering index (CRI/Ra)	80-89	Luminaire with limited surface temperature, class "D" in acc. with EN 60598-2-24	No
Colour temperature switchable	No	Outer diameter (mm)	167
Compatible with Amazon Alexa	No	Photobiological safety according to EN 62471	RG0
Compatible with Apple HomeKit	No	Power factor	0.5
Compatible with Google Assistant	No	Protection class according to IEC 61140	II
Control gear	LED driver constant current	Rated life time L70/B50 at 25 °C (h)	40000
Control gear included	Yes	Recess height/depth (mm)	62
Dimming 0-10 V	No	Stroboscope effect value SVM	0.006
Dimming 1-10 V	No	Suitable for ceiling mounting	Yes
Dimming DALI	No	Suitable for emergency lighting	No
Dimming DALI-2	No	Suitable for light line configuration	No
Dimming DMX	No	Suitable for recessed mounting	No
Dimming DSI	No	Suitable for surface mounting	Yes
Fit for workplace acc. EN 12464-1	No	Suitable for suspended mounting	No
Flickering value Pst LM	0.016	Type of grid	None
Height/depth (mm)	62	Width (mm)	167
Housing material	Other	With air slots	No
IFTTT support available	No	With light sensor	No
Impact resistance (IK rating)	IK06	With movement sensor	No
Light distribution	Symmetric		

FURTHER DETAILS

Product Status (at download): Active

Date Updated: 22-11-2024

Trade Tariff Commodity Code: 9405109890

Country of Origin: CN

Aurora Lighting UK, Apex Park, 6 Little Burrows, Burrowfields, Welwyn Garden City, AL7 4SW
01727 83 66 11 info@auroralighting.com https://auroralighting.com/

Disclaimer

- This Data Sheet was downloaded from EDATA - www.edata.org.uk - the UK electrotechnical industry data pool managed by EDA Data Services Limited on behalf of the Electrical Distributors' Association, on 19/11/2026.
- All intellectual property rights in the Product Data shown in this Data Sheet remains at all times the property of the Manufacturer named on the Data Sheet
- Product Data shown on the Data Sheet is for the product as supplied by the Manufacturer. Any subsequent modification of the product may affect specification and performance.
- Every reasonable effort is made to ensure accuracy of the Product Data which is believed to be correct at the date of download from EDATA. However neither the Manufacturer, the Wholesaler who downloaded the Data Sheet, nor EDA Data Services warrant the accuracy of the Product Data.
- The Product Data shown on the Data Sheet is not contractually binding. The Manufacturer reserves the right to amend the Product Data without prior notice.