Code: LGX2XLEDITB100AB-SB Linea-Georgian CFX | LINEA-GEORGIAN CFX RANGE | 100W LED Dimmers

Product Image



Wiring

Dimensions



Insert Type	2 gang 100W LED Trailing/Leading Edge Push On/Off Rotary 2 Way Switching Dimmer
Insert Colour	Antique Brass
EAN13 Barcode	5017504083366
Commodity Code	85365015
Luckins TSI	403376975
ETIM Class	EC000025
Dimensions(Nominal)	Single: Height = 95.5mm Width = 95.5mm Depth = 4.0mm
Fixing Hole Centres	Box Fixing = 60.3mm Grid Fixing = CFX Clips
Minimum Wall Box Depth	35mm
Switched Poles	Single
Current Rating	0.3A Per Gang
Voltage	230V AC
Maximum Load	5-70W Per Gang
Mains Frequency	50Hz
IP Rating	IP2XD
Terminal Capacity 1	2X1mm ²
Terminal Capacity 2	2X1.5mm²
Terminal Capacity 2 Earth Terminal Capacity 1	2X1.5mm² 5x1mm²
Earth Terminal Capacity 1	5x1mm ²
Earth Terminal Capacity 1 Earth Terminal Capacity 2	5x1mm ² 4X1.5mm ²
Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3	5x1mm ² 4X1.5mm ² 3X2.5mm ²
Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4	5x1mm ² 4X1.5mm ² 3X2.5mm ² 1X4mm ² Multi-Strand
Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5	5x1mm ² 4X1.5mm ² 3X2.5mm ² 1X4mm ² Multi-Strand 1X6mm ²
Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating	5x1mm ² 4X1.5mm ² 3X2.5mm ² 1X4mm ² Multi-Strand 1X6mm ² Face plate must be earthed
Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature	5x1mm ² 4X1.5mm ² 3X2.5mm ² 1X4mm ² Multi-Strand 1X6mm ² Face plate must be earthed -5°C to +40°C
Earth Terminal Capacity 1 Earth Terminal Capacity 2 Earth Terminal Capacity 3 Earth Terminal Capacity 4 Earth Terminal Capacity 5 Product Class 1 Ambient Operating Temperature Recommended Location Maximum Installation	5x1mm ² 4X1.5mm ² 3X2.5mm ² 1X4mm ² Multi-Strand 1X6mm ² Face plate must be earthed -5°C to +40°C Internal Use Only

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088

E: info@hamilton-litestat.com | **W:** www.hamilton-litestat.com (WEB)

All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. This datasheet was generated on 09/12/2024 E&OE



Code: LGX2XLEDITB100AB-SB Linea-Georgian CFX | LINEA-GEORGIAN CFX RANGE | 100W LED Dimmers

Patents And Trade Marks

Linea is a Registered Trade Mark No 2398665 CFX is a Registered Trade Mark No 2398667 Patent No. GB 2383375B Linea-Georgian CFX is a UK Registered Design Certificate No. R21 = 2078674 SS2 = 2078673

R Hamilton & Co Ltd, Unit 10 Carrick Business Centre, 4-5 Bonville Road, Brislington, Bristol, BS4 5NZ

T: +44 (0)1747 860088

E: info@hamilton-litestat.com | **W:** www.hamilton-litestat.com (WEB)

All accessories are manufactured under an accredited BS EN ISO 9001:2015 Quality Management System. It is the policy of the company to improve products as part of our development programme. Therefore, we reserve the right to alter designs and dimensions without prior notice. Illustrations and diagrams are reproduced within the limitations of reproduction and printing process and are not binding. Due to manufacturing processes we cannot guarantee an exact colour match and shadings of certain finishes. This datasheet was generated on 09/12/2024 E&OE