



Specially Developed to meet the requirements of EV charge points with data connectivity



Available in both CarbonTek<sup>®</sup> PVC Tuff-Sheathed or CarbonTek<sup>®</sup> SWA variants.

**Conductor:** Plain Annealed Copper Class 2 Stranded to BS EN 60228

**Insulation:** Thermosetting XLPE Type GP8 to BS 7655-1.3

**Bedding:** CarbonTek<sup>®</sup>

**Steel Wire Armour:** Galvanised steel wire armour (where applicable)

**Sheathing:** CarbonTek<sup>®</sup>

**Energy Monitor Cable:** Cat5e FTP—Foil Screened 4 twisted pair

Now using  
**CARBONTEK<sup>®</sup>**

## Manufactured in the UK

This cable is designed for use in the installation of electric vehicle charge points. The cable incorporates power conductors and an enhanced Cat 5 screened data cable, encapsulated in a double sheathed design for extra protection. Whilst designed for use in electric vehicle charge points, the cable is also suitable for other installations where power and data is required.

Also available with two Cat5e data cables to satisfy various installations.


These cables are designed to be installed in air, clipped to surface, on cable tray/ladder work and embedded in concrete. The cables can be laid direct in the ground providing that suitable mechanical protection is in place.

### STANDARD CORE COLOURS

3 core   
5 core 

 **MINIMUM  
OPERATING  
TEMPERATURE**  
**-15°C**

 **MAXIMUM  
OPERATING  
TEMPERATURE**  
**90°C**

 **MINIMUM  
BENDING  
RADIUS**  
**8xØ**

**The British Cable Company You Can Trust**



Sales Office: Millfield Industrial Estate, Arksey Lane, Bentley, Doncaster, South Yorkshire, DN5 0SJ  
Tel: 01302 821700 Email: [sales@doncastercables.com](mailto:sales@doncastercables.com)



Specially Developed to meet the requirements of EV charge points with data connectivity



### Dimensional Details:

Product Code	Number and nominal CSA of conductors	Nominal stranding of conductor	Nominal radial thickness of insulation	Nominal overall diameter of bedding	Galv. Steel Wire Armour	Nominal radial thickness of sheath	Approx. overall diameter	Approx. weight
EV-ULTRA3C4.0CAT5	3 x 4.0mm <sup>2</sup> + Cat5e FTP	7/0.85mm	0.7mm	12.5mm	N/A	1.0mm	15.0mm	389kg/km
EV-ULTRA3C4.0CAT5SWA	3 x 4.0mm <sup>2</sup> + Cat5e FTP	7/0.85mm	0.7mm	12.5mm	0.9mm	1.0mm	16.8mm	568kg/km
EV-ULTRA3C6.0CAT5	3 x 6.0mm <sup>2</sup> + Cat5e FTP	7/1.04mm	0.7mm	13.6mm	N/A	1.0mm	16.4mm	497kg/km
EV-ULTRA3C6.0CAT5SWA	3 x 6.0mm <sup>2</sup> + Cat5e FTP	7/1.04mm	0.7mm	13.6mm	1.25mm	1.0mm	19.0mm	823kg/km
EV-ULTRA3C710CAT5	3 x 10.0mm <sup>2</sup> + Cat5e FTP	7/1.35mm	0.7mm	15.0mm	N/A	1.0mm	17.6mm	532kg/km
EV-ULTRA3C710CAT5SWA	3 x 10.0mm <sup>2</sup> + Cat5e FTP	7/1.35mm	0.7mm	15.0mm	1.25mm	1.0mm	20.2mm	873kg/km
EV-ULTRA3C716CAT5	3 x 16.0mm <sup>2</sup> + Cat5e FTP	7/1.70mm	0.7mm	17.4mm	N/A	1.0mm	20.0mm	753kg/km
EV-ULTRA3C716CAT5SWA	3 x 16.0mm <sup>2</sup> + Cat5e FTP	7/1.70mm	0.7mm	17.4mm	1.25mm	1.0mm	22.5mm	1133kg/km
EV-ULTRA5C6.0CAT5	5 x 6.0mm <sup>2</sup> + Cat5e FTP	7/1.04mm	0.7mm	15.5mm	N/A	1.0mm	17.9mm	536kg/km
EV-ULTRA5C6.0CAT5SWA	5 x 6.0mm <sup>2</sup> + Cat5e FTP	7/1.04mm	0.7mm	15.5mm	1.25mm	1.0mm	20.5mm	873kg/km
EV-ULTRA5C710CAT5	5 x 10.0mm <sup>2</sup> + Cat5e FTP	7/1.35mm	0.7mm	18.4mm	N/A	1.0mm	19.8mm	746kg/km
EV-ULTRA5C710CAT5SWA	5 x 10.0mm <sup>2</sup> + Cat5e FTP	7/1.35mm	0.7mm	18.4mm	1.25mm	1.0mm	23.4mm	1121kg/km
EV-ULTRA5C716CAT5SWA	5 x 16.0mm <sup>2</sup> + Cat5e FTP	7/1.70mm	0.7mm	21.7mm	1.25mm	1.0mm	27.7mm	1807kg/km

Weight and dimensional information is provided as an approximate guide only.

**Sales Office: Millfield Industrial Estate, Arksey Lane, Bentley, Doncaster, South Yorkshire, DN5 0SJ**  
**Tel: 01302 821700 Email: [sales@doncastercables.com](mailto:sales@doncastercables.com)**





Specially Developed to meet the requirements of EV charge points with data connectivity



### Dimensional Details: EV-Ultra Plus

Product Code	Number and nominal CSA of conductors	Nominal stranding of conductor	Nominal radial thickness of insulation	Nominal overall diameter of bedding	Galv. Steel Wire Armour	Nominal radial thickness of sheath	Approx. overall diameter	Approx. weight
EV-ULTRAPLUS3C6.0	3 x 6.0mm <sup>2</sup> + Cat5e FTP + Cat5e FTP	7/1.04mm	0.7mm	15.7mm	N/A	1.0mm	18.2mm	600kg/km
EV-ULTRAPLUS3C6.0SWA	3 x 6.0mm <sup>2</sup> + Cat5e FTP + Cat5e FTP	7/1.04mm	0.7mm	15.7mm	1.25mm	1.0mm	20.6mm	890kg/km

### Electrical Properties:

	Single Phase			
	4.0mm <sup>2</sup>	6.0mm <sup>2</sup>	10.0mm <sup>2</sup>	16.0mm <sup>2</sup>
Maximum current rating (A)	45	58	80	107
Voltage drop (mV/A/m)	12	7.9	4.7	2.9

	3 Phase		
	6.0mm <sup>2</sup>	10.0mm <sup>2</sup>	16.0mm <sup>2</sup>
Maximum current rating (A)	52	71	91
Voltage drop (mV/A/m)	6.8	4.0	2.5

Current carrying capacities based on ambient temperature of 30°C and conductor operating temperature of 90°C.  
Refer to BS7671 for further details including grouping factors and ambient temperatures other than 30°C


### Features and Benefits

- Power and data combined in one cable
- Less storage space required
- Easier to handle
- Easier to route through walls and buildings
- Saves installation time
- Gives a cleaner, neater looking installation

**Sales Office: Millfield Industrial Estate, Arksey Lane, Bentley, Doncaster, South Yorkshire, DN5 0SJ**  
**Tel: 01302 821700 Email: [sales@doncastercables.com](mailto:sales@doncastercables.com)**







Specially Developed to meet the requirements of EV charge points with data connectivity



Running data and power in a single cable is a concern for many electricians, with most believing that segregation of power (Band II) and data (Band I) is always required.

It is however already common to find power and data inside one cable in many existing applications, an example is DALI networks which incorporate data within a 5 core power cable.

It is recommended that the screening of the data cable is terminated to earth.

#### What do the regulations say?

**Voltage Band I** is defined as levels of voltage which are too low to provide serious electric shocks; effectively this limits the band to extra-low voltage (ELV), including telecommunications, signalling, bell, control and alarm circuits.

**Voltage Band II** is defined as all voltages which are used in electrical installations not included in Band I. This means that all 230V supplies are included in Band II.

**Proximity of electrical services** (extract from 528.1) - Except where one of the following methods is adopted, neither a Band I nor a Band II circuit shall be contained in the same wiring system as a circuit of nominal voltage exceeding that of low voltage, and a Band I circuit shall not be contained in the same wiring system as a Band II circuit. (i) - Every cable or conductor is insulated for the highest voltage present.

EV-Ultra® consists of power conductors and data cables that are rated to the same nominal voltage – therefore segregation of power and data is not required.

**Proximity of communications cables** (extract from 528.2) - Special considerations of electrical interference, both electromagnetic and electrostatic, may apply to telecommunication circuits, data transfer circuits and the like.

EV-Ultra® has been designed with these considerations in mind, it incorporates screened, twisted pair data cables and is also constructed with a lay length that reduces interference. Laboratory and on-site installation tests have also been conducted and no interference or degradation of signal was recorded.