


## Wall Charger 2 Tethered


- Auto Solar Charging allowing you to utilise excess solar power to charge your EV, maximising the benefits of clean, renewable energy while reducing your energy bills.
- Tariff Sense Our energy management feature connects to any UK tariff, giving real-time insights and control over charging costs.
- Models with Wi-Fi/LAN, Wi-Fi/LAN/4G
- Fully compliant with The Electric Vehicles (Smart Charge Points) Regulations 2021, including Schedule 1
- Full Smart functionality via Smart App and OCPP 1.6J connectivity
- Dynamic charging up to 7.4kW (32A)
- No earth rod required integrated open PEN conductor protection
- Safe integrated 30mA Type A RCD with 6mA DC
- OCPP 1.6J connectivity free lifetime over-the-air updates
- 7.5m of cable and Type 2 connector
- Socketed 7.4 & 22kW versions also available



PART NO.	DESCRIPTION	TYPE	MAX OI (kw)	JTPUT (A)	INPUT VOLTAGE
EVWC2T7G-02	Single Phase 7.4kW / WI-FI / LAN	Tethered Type 2 Plug 7.5m Cable	7.4kW MODE 3	32A	220-240V
EVWC2T7GG-02	Single Phase 7.4kW / WI-FI / LAN / 4G	Tethered Type 2 Plug 7.5m Cable	7.4kW MODE 3	32A	220-240V











FI FCTR	SPECIE	ICAT	IONS

ELECTRICAL SPECIFI	ICATIONS				
MAXIMUM CHARGE CURRENT	Configurable, 6-32A	LOAD BALANCING	Supplied with Load Management Kit		
INPUT FREQUENCY	50-60hz	OVERLOAD AND FAULT PROTECTION	Over current and load protection		
PEN FAULT	Built-in, Earth Disconnection	METER ACCURACY	2% Class C equivalent internal meter with option for connection to external RS485 MDBUS Meter		
RCD PROTECTION	Built-in 30mA AC Type A Protection	TERMINALS	Combi screw first fix plug connector		
ELECTRICAL CLASS	Class 1 with Class 2(II) Housing	INDICATOR	RGB LED and Buzzer		
CONSUMER UNIT REQUIREMENTS	40A MCB or 30mA Type A RCD (Dependent on cable type &/or route)	INDICATOR MODES	BLUE – Standby, FLASHING BLUE – Preparing, GREEN – Charging, YELLOW – No Network, RED – Error, PURPLE – Balancer Error		
CABLE MANAGEMENT	Built-in cable wrap & Gun holster	ANTI TAMPER DETECTION	2 Layer Protection, Bluetooth to Bluetooth commissioning		
OPERATING CONDITI	IONS & CONSTRUCTION				
OPERATING	-25 to +55℃	HOUSING	UV Stabilised Polycarbonate		
IP RATING	IP65	COLOUR	Base and Body RAL 9005 (Black) Trim RAL 9006 (Anthracite Grey) Optional Coloured Trims available as accessories		
IK RATING	IK 10	DIMENSIONS	305 (H) x 201 (W) x 115 (D)		
MOUNTING	Wall Mounted, 4-point with horizon- tal and vertical adjustment, 110mm x 145mm fixing centres				
CONNECTIVITY & AC	CCESSORIES				
SOC MODULE	AI ESP32-S SOC	SOFTWARE & FIRMWARE UPDATE	Over-the-air		
WI-FI & ETHERNET	2.4Ghz 802.11 B/G/N & RJ45	STANDARDS & APPROVALS	IEC61851-1, IEC61439-7, IEC 62955, IC 61851-21-2, BS EN62196, EN301 511, EN 301 908-1/2/13, EN		
WI-FI SECURITY	WPA/WPA2/WPA2-ENTERPRISE/WPS		301 489-3, EN 300 330, EMC COMPLIANT, CE, UKCA, The Electrical Vehicles (Smart Charge Points) Regulations 2021 including schedule 1		
BLUETOOTH	4.2 BR/EDR and BLE	SUPPLIED	5 x Base Fixing Washers, 5 x Assembly		
CONNECTION PROTOCOL	OCPP 1.6J	ACCESSORIES	Lid Bolts, 1 x Blanking Plug and 1 x 25mm Compression Gland, User-side Connector, Cord Grip and 2 x Cord Grip Assembly Screws		
4G DATA	Model specific 3 years included when used with Sync Energy (on the included package). Top-up online to continue service after 3 years.	ACCESSORIES	Single Charger Stand - (EVASTAND12S) Twin Charger Stand - (EVASTAND12T) Charging Cables - Various Coloured Trims - Shown below		
APP	Powered by Sync Energy				

EVWC2Txx.NH.11.2024