## RUBBER

LOW VOLTAGE **FILLERS** 

**SKY PLAST BECOMES** RUBBER **IN 5 MINUTES** 

Ray

**Tech** 

## **SKY PLAST**

Two-component insulating rubber, mouldable, selfextinguishing paste with high dielectric characteristics.

Sky Plast is ideal for covering, protecting, insulating, finishing and fireproofing any electrical and non-electrical component. Once the 2 components have been blended in a ratio of 1:1 (for max 2 min.) until uniform, it cross links quickly at room temperature in less than 5 minutes. After being wrapped around the component to be protected, Sky Plast guickly transforms into a layer of rubber with high dielectric and self-extinguishing characteristics.

## **ADVANTAGES**

- ▶ Low smoke and toxic and corrhosive gases emission.
- > Able to replace taping, heat-shrinking, resin finishes.
- Flexible and elastic.
- Quickly ready for use.









Insulation of multiple connections



Conduit protection



Preparation of deflectors, nozzles, flow deviators

Total quantity
250 gr
500 gr



Creation of LV terminals





Preparation on-site of expanders for inserts



of small moulds

**PRODUCT / Item SKY PLAST 250** SKYPLAST250 SKY PLAST SKYPLAST





Drop line, bar, transformer through insulation







On-site preparation of braces and supports

Package type

2 cans

2 cans