




General Information

Dimensions (mm)	Ø132 x 60.5
Colour	White
Materials	UL94-V0 rated UV stabilised ABS
Mounting	Ceiling
Recommended Installation Locations	Living Areas, Loft Areas, Bedrooms, Escape Routes & Stairways
Indication	2 LEDs; Yellow - Fault, Red - Fire
Auto Dim Power LED	No
Manual Test Button	Checks sensor, electronics & sounder
Weight (Kg)	0.253
Warranty (Years)	5

Technical

Sensor Type	Multi Sensor; Sensor 1 - Optical Smoke Sensor 2 - Heat
Heat Detection Class	A1
Heat Detection Temperature (°C)	58
Sounder Output (dB)	85 @ 3m
Hush Function	Alarm hush - 10 minutes, Fault hush - 12 hours
Installation Grade	F1

Supply, Power & Backup

Supply Type	Battery Powered
Operating Voltage (V DC)	3
Battery Backup	Non-replaceable 10 Year Battery
Battery Type	3V Lithium
Battery Size	CR17450
Battery Chemistry	Lithium
Battery Lifetime	10 Year

Interconnectability

Wired Interconnect Supported	No
RF-LINK Supported	Yes; Requires ES1RF2
Maximum Supported Wired & RF-LINK Interconnected Devices	28

Environment

Operating Temperature (°C)	0 to +40
Relative Humidity Resistance (%)	95 (non-condensing)

Standards EN 14604: 2005 +AC: 2008, BS 5446-2: 2003

Accessories

ES1RF2: Alarm RF-Link Module 2
 ES1MP: Alarm Masking Plate
 ES1MTW: Alarm Multi Tool (2 Pack) White
 ES1MTB: Alarm Multi Tool (2 Pack) Black

Features

Dust compensation
 Insect mesh
 Lock-in base
 24 hour memory function
 Clear LED indication status