


Product Code: ES1RB

Description: Hardwired Interconnect Relay Base


General Information

Dimensions (mm)	Ø142 x 36.5
Colour	White
Materials	UL94-V0 rated UV stabilised ABS
Mounting	Ceiling or Wall
Weight (Kg)	0.18
Warranty (Years)	5

Supply, Power & Backup

Supply Type	Mains AC with battery backup
Supply Voltage (V AC)	230
Frequency (Hz)	50
Cable Size (mm ²)	0.75 – 2.5
Relay Voltage - Maximum (AC)	250
Maximum Switchable Load (A)	8
Relay/Contact Type	Volt free SPDT
Maximum Power Consumption (W)	3
Standby Power Consumption (W)	0.38
Battery Backup	Non-replaceable Rechargeable
Battery Type	3V Lithium (x2)
Battery Size	VL2330
Battery Chemistry	Lithium

Interconnectability

Wired Interconnect Supported	Yes
Maximum Interconnect Wiring Distance (m)	300
RF-LINK Supported	No
Maximum Supported Wired & RF-LINK Interconnected Devices	28

Environment

Operating Temperature (°C)	0 to +40
----------------------------	----------

Compatible Products Compatible with Interconnect supported Espire Products

Features

- Switch 3rd Party devices when alarm activates
- Multiple knockout entries
- Compatible with any Espire hardwired interconnect supported alarms
- Supports Espire Alarms to be mounted on top
- Comes supplied with cover when not used to mount Espire alarms
- Backup battery can power the base up to 2 months in standby