


Technical Specification



Product Code: ES1REMV

Description: Hardwired Interconnect Remote Controller





| General Information | |
|--|---|
| Dimensions (mm) | 86 x 86 x 61 (Backbox Included) |
| Colour | White |
| Materials | Urea |
| Mounting | Single Pattress – Surface and Flush Mounting (backbox included) |
| Weight (Kg) | 0.24 |
| Warranty (Years) | 5 |
| Supply, Power & Backup | |
| Supply Type | Mains AC |
| Supply Voltage (V AC) | 230 |
| Frequency (Hz) | 50 |
| Cable Size (mm²) | 0.75 - 2.5 |
| Maximum Power Consumption (W) | 0.5 |
| Standby Power Consumption (W) | 0.2 |
| Interconnectability | |
| Wired Interconnect Supported | Yes |
| Maximum Interconnect Wiring Distance (m) | 300 |
| RF-LINK Supported | No |
| Maximum Supported Wired & RF-LINK Interconnected Devices | 28 |
| Environment | |
| Operating Temperature (°C) | 0 to +40 |
| Relative Humidity Resistance (%) | 95 (non-condensing) |
| Compatible Products Interconnect supported Espire Products | |

Features

3 switches for; testing the alarms, to activate the hush function on & to activate the locate function Compatible with any Espire Interconnect supported Alarms
Designed to fit standard UK 1 Gang mount box





