

	EV CHARGER DISTRIBUTION BOARDS					
PART NUMBER	EV32AXBD	EV40AXBD	EV32B	EV40B		
GTIN-13	5060523526208	5060523526222	5060523524297	5060523524303		
BI DIRECTIONAL	Y	Y	Y	Y		
RATING (A)	32A	40A	32A	40A		
RATED RESIDUAL OPERATING CURRENT (IΔn)	30mA	30mA	30mA	30mA		
RCBO /RCD TYPE	TYPE A (RCBO)	TYPE A (RCBO)	TYPE B (RCD)	TYPE B (RCD)		
MCB RATING/ Tripping Curve	B CURVE	B CURVE	32A B CURVE	40A B CURVE		
NUMBER OF POLES	1P+N (SW)	1P+N (SW)	2	2		
T2 SPD	Y	Y	N	N		
DIMENSION DRAWING	6P	6P	6P	6P		
WEIGHT (1PC) Kg	2.5	3	3	3		
DIMENSIONS (HxWxD)mm	259x162x113	259x162x113	259x162x113	259x162x113		
DC MAX	6mA	6mA	10mA	10mA		
STANDARD	EN 61439-3					
RATED VOLTAGE (Un/AC)	230V					
FREQUENCY (Hz)	50/60					
PROTECTION DEGREE (IP)	2XC					
MAXIMUM TERMINAL BAR CAPACITY	16mm²					
TERMINAL BAR TIGHTENING TORQUE (Nm)	2.0					
MOUNTING	35mm DIN RAIL					
MATERIAL	1mm ELECTRO GALVANISED STEEL (ZINC)					
FINISH	RAL 9001 POWDER COATED SMOOTH FINISH					
ACCESSORY PACK (6P)	CIRCUIT IDENTIFICATION LABELS / GROMMET STRIP					
ORIGIN OF MANUFACTURE	CHINA					
<i>*please note these units are not supplied with a tail clamp and it cannot be retro fitted.</i>						

**please note these units are not supplied with a tail clamp and it cannot be retro fitted.*

DIMENSIONS

