

Luminaires | Downlights

**Poly-SlimCS™ 9W Colour
Switchable Round
Polycarbonate Low
Profile Downlight**



AU-PLPC09CS

Photometrics

Wattage	9
Lumens	850 - 950
Lm/W	106
Beam Angle	120
Colour Temperature	3000 / 4000 / 6500
RA	80
SDCM	<6

Product Features

Brand	Aurora
IP Rating	IP40
IK Rating	IK02
L70 Hours	L70 40,000
Lifetime Class	B50
SKU Type	Non Dim
Dimmable	NO
Warranty	3 Years
Country of origin	cn

Electrical Specification

Input Voltage (Min)	220
Input Voltage (Max)	240
Output Voltage	240
Input Voltage Type	v
Power Factor	0.5
Surge Protection (kV)	1500v
Protection class	Class 3
Frequency (Min) Hz.	50
Frequency (Max) Hz.	60
Operating Temp. (Min) °C	-20
Operating Temp. (Max) °C	40

Physical Attributes

Length (mm)	146
Height (mm)	25
Overall Diameter (mm)	146
Cutout Diameter Min. (mm)	130
Cutout Diameter Max. (mm)	130
Product Weight (KG)	0.176
Optic Material	pc+pc+al
Finish Colour	White