

Luminaires | Downlights

**Poly-SlimCS™ 12W
Colour Switchable
Round Polycarbonate
Low Profile Downlight**

AU-PLPC12CS



Photometrics

Wattage	12
Lumens	1200 - 1300
Lm/W	108
Beam Angle	120
Colour Temperature	3000 / 4000 / 6500
RA	80
SDCM	<6

Product Features

Brand	Aurora
IP Rating	IP40
IK Rating	IK02
L70 Hours	L70 40,000
Lifetime Class	B50
SKU Type	Non Dim
Dimmable	NO
Warranty	5 YEARS
Country of origin	CN

Electrical Specification

Input Voltage (Min)	220
Input Voltage (Max)	240
Input Voltage Type	AC
Power Factor	0.5
Surge Protection (kV)	1500
Protection class	CLASS3
Frequency (Min) Hz.	50HZ
Frequency (Max) Hz.	60HZ
Operating Temp. (Min) °C	-20
Operating Temp. (Max) °C	40

Physical Attributes

Length (mm)	170
Width (mm)	25
Height (mm)	25
Overall Diameter (mm)	170
Cutout Diameter Min. (mm)	150
Cutout Diameter Max. (mm)	150
Product Weight (KG)	0.222
Material	PC+PA+AL
Finish Colour	White