

Luminaires | Downlights

**Poly-SlimCS™ 18W  
Colour Switchable  
Round Polycarbonate  
Low Profile Downlight**

AU-PLPC18CS



Photometrics

<b>Wattage</b>	18
<b>Lumens</b>	1850 - 2000
<b>Lm/W</b>	111
<b>Beam Angle</b>	120
<b>Colour Temperature</b>	3000 / 4000 / 6500
<b>RA</b>	80
<b>SDCM</b>	<6

Product Features

<b>Brand</b>	Aurora
<b>IP Rating</b>	IP40
<b>IK Rating</b>	IK02
<b>L70 Hours</b>	L70 40,000
<b>Lifetime Class</b>	B50
<b>SKU Type</b>	Non Dim
<b>Dimmable</b>	NO
<b>Warranty</b>	3 YEARS
<b>Country of origin</b>	CN

## Electrical Specification

<b>Input Voltage (Min)</b>	220
<b>Input Voltage (Max)</b>	240
<b>Input Voltage Type</b>	AC
<b>Power Factor</b>	0.5
<b>Surge Protection (kV)</b>	1500KV
<b>Protection class</b>	CLASS 3
<b>Frequency (Min) Hz.</b>	50HZ
<b>Frequency (Max) Hz.</b>	60HZ
<b>Operating Temp. (Min) °C</b>	-20
<b>Operating Temp. (Max) °C</b>	40

## Physical Attributes

<b>Length (mm)</b>	224
<b>Width (mm)</b>	25
<b>Height (mm)</b>	25
<b>Overall Diameter (mm)</b>	224
<b>Cutout Diameter Min. (mm)</b>	210
<b>Product Weight (KG)</b>	0.356
<b>Material</b>	PC+PA+AL
<b>Finish Colour</b>	White