

Product Code: 26404

Description: Standard 4 Module 4 Channel, 7 Day Timer, 300 Operations



General Information

Dimensions (mm)	90 x 36 x 63
Display	LCD Display
Time Base	Quartz Crystal
Quartz Crystal Accuracy (at 20°C)	≤ ± 0.5 Seconds / Day
Materials	Self-Extinguishing Thermoplastic
Mounting	Surface Mounting or DIN
Distribution Board Mounting	35mm DIN-rail (DIN EN 60715)
Module Size	4
Warranty (Years)	3

Programming

Programming Schedule	24 Hour, and 7 Day Programmable
Available Operations	300 Operations
Switching Modes	ON, OFF; Pulse, Cycle
Minimum Interval (Mins)	1
Summer/Winter Time Change	Yes (Automatic)
Program Security	Unlimited (E2-PROM)
Pulse length - Pulse function (switching time)	00:01 up to 59.59 mm:ss
Pulse length - Timer (man. switching)	0:00:01 up to 9:59:59 h:mm:ss

Supply & Power

Supply Voltage (V AC)	230
Power Consumption (W)	0.2-1
Cable Size (mm²)	0.5 - 2.5
Power Reserve @ 20°C	10 Years (Approx.)
Battery Type	Replaceable CR2032
IEC Protection Class	Class II When Installed According to Regulations

Environment

Ingress Protection	IP20
Operating Temperature (°C)	-30 to +55

Features

Volt-Free 16A Changeover Contact
 300 Memory Locations
 Module Timer: Multiple Applications from One Switch
 Standard Programming
 Works with key Programming & EasyVUE Connect (Key & Hub are Optional Extras)
 Battery Reserve: 10 Years
 Extra Functions - Channel Key Assignment, Accepts External Inputs

Outputs

Number of Outputs	4
Total Switch Rating	(4 x) 16 (6) A
Contact Type	SPDT
Contact Material	AgSnO ²
Maximum Starting Current (A)	50
Minimum Switching power (mW)	1000 (10V/10mA)

Accessories

143541: Module Enclosure
 25195: Easy Vue Hub Programming Interface
 25196: Easy Vue Hub Programming Interface with Bluetooth
 25193: Programming Interface

