

Product Code: CHOICE RSTAT5RF

Description: Wireless Digital Display Programmable Thermostat



Component 1

Wireless Digital Programmable Thermostat Transmitter

Quantity 1

Component 2

Wireless Thermostat Receiver

Quantity 1

General Information

| | |
|-----------------------------------|--------------------------------|
| Dimensions (mm) | 110 x 104 x 21.5 |
| Finish | White |
| Materials | ABS |
| Mounting | Surface or free standing |
| Call for Heat Indication | LCD Display |
| Supply & Power | |
| Battery Specification | AAA (x4) |
| Battery Low Indicator | Yes |
| Programming | |
| Adjustment Type | Comfort / Economy |
| Programming Schedule | 24 Hour or 7 Days |
| Set Temperature Range (°C) | 0 to 50 |
| Temperature Display Range (°C) | 5 to 35 |
| Temperature Swing Adjustment (°C) | +/-0.5 or +0/-0.1 (Selectable) |
| Minimum Interval (Mins) | 10 |
| Timing Accuracy | <1 sec Per Day |
| Network | |
| Transmission Frequency (MHz) | 868 |
| Wireless Range - Open Field (m) | 80 |
| Wireless Range - Indoor (m) | 30 |
| Environment | |
| Ingress Protection | IP30 |
| Operating Temperature (°C) | 0 to +50 |
| Frost Protection | Yes (5°C) |

General Information

| | |
|---------------------------------|-------------------------------------|
| Dimensions (mm) | 88 x 88 x 39.4 |
| Finish | White |
| Materials | ABS |
| Mounting | Surface |
| Supply Voltage (V AC) | 230 |
| Frequency (Hz) | 50 |
| Cable Size (mm ²) | 0.5- 1.5 (Flex) 0.5- 2.5 (Rigid) |
| Network Connection Type | Radio Frequency |
| Transmission Frequency (MHz) | 868 |
| Wireless Range - Open Field (m) | 80 |
| Wireless Range - Indoor (m) | 30 |
| Output Relay Rating | 16A (@250V AC) Volt Free Contact |
| IEC Protection Class | II |
| Ingress Protection | IP30 |
| Operating Temperature (°C) | 0 to +50 |

Warranty Years 3

