

Product Code: UDTAKITSS

Description: Indication, Pull Cord and Reset Modules for Assistance Alarm Kit



Component 1 Description	Quantity	Component 2 Description	Quantity
UDTAPCMSS - Pull Cord Module	1	UDTAPLBMSS - Power, Light and Buzzer Module	1

General Information	
Dimensions (mm)	87 x 87 x 41
Finish	Steel Grey
Pull Cord Length (m)	3 (Including 2 Triangular Bangles)
Plate Size	Single Gang
Materials	Stainless Steel (Grade 304)
Mounting	Surface or Flush (Surface Box Not Included)
Anti-Ligature	Yes
Supply & Power	
Operating Voltage (V DC)	12
Maximum Cable Size (mm ²)	1.5
Power Consumption (W)	0.3
Environment	
Ingress Protection	IP20

General Information	
Dimensions (mm)	87 x 87 x 41
Plate Size	Single Gang
Finish	Steel Grey
Materials	Stainless Steel (Grade 304)
Mounting	Surface or Flush (Surface Box Not Included)
Indication	LED illuminates in red when in alarm state
Activated Buzzer Sound Level (db)	>80
Purpose	Activation and Reset Circuits
Maximum Cable Size (mm ²)	1.5
Power Consumption (A)	0.2
Battery Backup	A23 Battery
Input Type	Ground & 2 live circuits - X1 & X2
Activation Type	Energise with a Normally Open Clean Contact
Output Type	1 Switched Live sharing common ground Separate output for additional sounders
Number of Outputs	2
Output Rating	12V 500mA
Ingress Protection	IP20

Component 3 Description	Quantity
UDTAREMSS - Assistance Alarm Reset Module	1

General Information	
Dimensions (mm)	87 x 87 x 41
Plate Size	Single Gang
Finish	Steel Grey
Materials	Stainless Steel (Grade 304)
Mounting	Surface or Flush (Surface Box Not Included)
Indication	LED illuminates in red when in alarm state
Buzzer Sound Level When Activated (db)	>80
Operating Voltage (V DC)	12
Maximum Cable Size (mm ²)	1.5
Power Consumption (W)	0.9
Ingress Protection	IP20

Warranty Years	2
Additional Information	If mounting surface you will need UDTASMBSS Surface Mount Back Box.

