



General Information

Dimensions (mm)	87 x 87 x 41
Plate Size	Single Gang
Finish	White
Materials	Anti-Microbial ABS
Mounting	Surface or Flush (Surface Box Included)
Indication	LED illuminates in red when in alarm state
Buzzer Sound Level When Activated (db)	>80
Purpose	Activation and Reset Circuits
Warranty (Years)	2

Supply & Power

Operating Voltage (V AC)	100 - 230
Maximum Cable Size (mm²)	1.5
Power Consumption (A)	0.2
Battery Backup	A23 Battery

Inputs

Input Type	Ground & 2 live circuits - X1 & X2
Activation Type	Energise with a Normally Open Clean Contact

Outputs

Number of Outputs	2
Output Type	1 Switched Live sharing common ground Separate output for additional sounders
Output Rating	12V 500mA

Environment

Ingress Protection	IP20
---------------------------	------

Supplied 1 x Backbox, Installation Bolts, User Manual

Features

Built in Battery Backup with Supplied A23 Battery
Sounder Buzzes Intermittantly When Battery Needs Replacing
Anti-Microbial Properties

Accessories

UDTAPLBM: Assistance Alarm, Power, Light and Buzzer Module
UDTALBM: Assistance Alarm Light and Buzzer Module
UDTAPCM: Assistance Alarm Pull Cord Module
UDTASPC: Assistance Alarm Replacement Pull Cord
UDTAREM: Assistance Alarm Reset Module