# beacon®

## Technical Specification

**ESP** ScolmoreGROUP

**Product Code:** UDTAPLBMSS
**Description:** Stainless Steel Assistance Alarm, Power, Light and Buzzer Module

### General Information

| | |
|---|---|
| Dimensions (mm) | 87 x 87 x 41 |
| Plate Size | Single Gang |
| Finish | Steel Grey |
| Materials | Stainless Steel (Grade 304) |
| Mounting | Surface or Flush (Surface Back Box Not Included) |
| Indication | LED illuminates in red when in alarm state |
| Buzzer Sound Level When Activated (db) | >80 |
| Purpose | Activation and Reset Circuits |
| Warranty (Years) | 2 |

### Supply & Power

| | |
|---|---|
| Operating Voltage (V AC) | 100 - 230 |
| Maximum Cable Size (mm²) | 1.5 |
| Power Consumption (A) | 0.2 |
| Battery Backup | A23 Battery |

### Inputs

| | |
|---|---|
| Input Type | Ground & 2 live circuits - X1 & X2 |
| Activation Type | Energise with a Normally Open Clean Contact |

### Outputs

| | |
|---|---|
| Number of Outputs | 2 |
| Output Type | 1 Switched Live sharing common ground<br>Separate output for additional sounders |
| Output Rating | 12V 500mA |

### Environment

| | |
|---|---|
| Ingress Protection | IP20 |

| | |
|---|---|
| **Supplied** | User Manual |

| | |
|---|---|
| **Additional Information** | If mounting surface you will need UDTASMBSS Surface Mount Back Box. |

| Features | Accessories |
|---|---|
| Built in Battery Backup with Supplied A23 Battery<br>Sounder Buzzes Intermittantly When Battery Needs Replacing | UDTAPLBMSS: Stainless Steel Assistance Alarm, Power, Light and Buzzer Module<br>UDTALBMSS: Stainless Steel Assistance Alarm Light and Buzzer Module<br>UDTAPCMSS: Stainless Steel Assistance Alarm Pull Cord Module<br>UDTASPCSS: Stainless Steel Assistance Alarm Replacement Pull Cord<br>UDTAREMSS: Stainless Steel Assistance Alarm Reset Module<br>UDTASMBSS: Stainless Steel Surface mount Box |

IP20  BATTERY BACK-UP  UKCA  CE  2 YEAR GUARANTEE